MW-13 GSI Job No. 1811013 KSA 82a-1212 ID No. 0050540 WATER WELL RECORD Form WWC-5 1 LOCATION OF WATER WELL: Fraction

County: Sumner SE ½ SE ½ SE ½

The description of well if located within circles. Township Number Section Number Range Number 32 2 11 Distance and direction from nearest town or city street address of well if located within city? Approx. 58' N, 20' W of NWC of Myrtle St. and Sumner Ave. - Oxford 2 WATER WELL OWNER: KDHE RR#, St. Address, Box # : 1000 SW Jackson St., Ste. 410 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Topeka, KS 66612 Application Number: 3 LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 45.5 ft. ELEVATION: 1189.50 (TOC)

Depth(s) Groundwater Encountered 1 39 ft. 2 ft. 3 ft. 03/06/15 Depth(s) Groundwater Encountered 1 39 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 38.34 ft. below TOC measured on mo/day/yr 03/06/15 - NF ---Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was fl. after hours pumping gpm
Bore Hole Diameter 8.25 in. to 45.5 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ĭë ë W 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X 8 Concrete tile 5 TYPE OF BLANK CASING USED: 5 Wrought Iron CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded **Flush** 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 30.5 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 Blank casing diameter 2 in. to 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 5 Fiberglass 8 RMP (SR) 11 Other (specify)
6 Concrete tile 9 ABS 12 None used (open hole)
5 Gauzed wrapped 8 Saw cut 11 None (open hole) 3 Stainless steel 2 Brass 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE: 3 Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 10 Other (specify) 2 Louvered shutter 7 Torch cut

 2 Louvered shutter
 4 Key punched
 7 Torch cut
 10 Other (specify)

 SCREEN-PERFORATED INTERVALS:
 From
 30.5
 ft. to
 45.5
 ft. From
 ft. to
 ft.

 4 Key punched From ft. to ft. From ft. to ft. 10 Livestock pens What is the nearest source of possible contamination: 14 Abandoned water well 1 Septic tank 7 Pit privy 4 Lateral lines 11 Fuel storage 15 Oil well/ Gas well 8 Sewage lagoon 2 Sewer lines 5 Cess pool 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedvard 13 Insecticide storage Direction from well? How many feet? LITHOLOGIC LOG CODE FROM FROM PLUGGING INTERVALS TO TO 1.5 0 Topsoil, sandy clay, dark brown 1.5 Sandy Clay, brown 贸 Silty Clay, red brown to brown, some 30 to trace fine sand 30 45.5 Sand, orange, fine to medium grained Survey date: 04/02/15; Datum: NAD83 Latitude: N 37.27564 Longitude: W 97.16933 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)

O3/03/15

Water Well Contractor's License No.

O3/03/15

Under the business name of GSI Engineering, LLC

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.