

1 LOCATION OF WATER WELL: County: Sumner		Fraction SW ¼ SW ¼ SW ¼	Section Number 12	Township Number T 32 S	Range Number R 2 E
Distance and direction from nearest town or city street address of well if located within city? Approx. 80' N, 56' E of NEC of Myrtle St. and Sumner Ave. – Oxford					
2 WATER WELL OWNER: KDHE RR#, St. Address, Box #: 1000 SW Jackson St., Ste. 410 City, State, ZIP Code: Topeka, KS 66612 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1 Mile W E N S X	4 DEPTH OF COMPLETED WELL 45.5 ft. ELEVATION: 1189.05 (TOC) Depth(s) Groundwater Encountered 1 38 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 38.78 ft. below TOC measured on mo/day/yr 03/06/15 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 45.5 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well				
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted				
	Water Well Disinfected? Yes No X				
	5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Flush Blank casing diameter 2 in. to 30.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30.5 ft. to 45.5 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 28.5 ft. to 45.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 3 ft. to 28.5 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/ Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	CODE	LITHOLOGIC LOG	FROM	TO
0	2		Topsoil, sandy clay, dark brown		
2	27.5		Silty Clay, dark brown to red brown to brown, some fine sand		
27.5	32.5		Clayey Sand, fine grained, gray/green/brown		
32.5	42		Sand, fine to coarse grained		
42	45.5		Shale, blue/green		
Survey date: 04/02/15; Datum: NAD83					
Latitude: N 37.27561					
Longitude: W 97.16868					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 03/03/15 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 04/17/15 under the business name of GSI Engineering, LLC by (signature) <i>Anni Orde</i>					

OFFICE USE ONLY

T

R

SEC