**MW-15** GSI Job No. 1811013 WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 0050542 1 LOCATION OF WATER WELL: Township Number Range Number Section Number Fraction SW ½ SW ½ SW ½ 12 **32** s R 2 County: Sumner Distance and direction from nearest town or city street address of well if located within city? Approx. 6' N, 120' E of NEC of Myrtle St. and Sumner Ave. - Oxford 2 WATER WELL OWNER: KDHE RR#, St. Address, Box # : 1000 SW Jackson St., Ste. 410 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Topeka, KS 66612 Application Number: City, State, ZIP Code : TOPERA, TO SOCIAL STATE OF COMPLETED WELL 3 LOCATON WITH 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: 1188.19 (TOC)

AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 39 ft. 2 38.9 ft. 3 ft. COCATON WITH 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION: 03/06/15 39 ft. 2 38.9 ft. 3 ft. WELL'S STATIC WATER LEVEL 38.63 ft. below TOC measured on mo/day/yr 03/06/15 -- NF ---Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8.25 in. to 40 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Σ W 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X submitted CASING JOINTS: Glued Clamped 5 Wrought Iron 8 Concrete tile 5 TYPE OF BLANK CASING USED: Welded 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 2 PVC 4 ABS 7 Fiberglass Threaded Flush

Blank casing diameter 2 in. to 25 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 4 ABS 7 PVC 10 Asbestos-cement

5 Fiberglass 8 RMP (SR) 11 Other (specify)

6 Concrete tile 9 ABS 12 None used (open hole)

5 Gauzed wrapped 8 Saw cut 11 None (open hole) 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 3 Stainless steel 2 Brass 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE: 3 Mill slot 6 Wire wrapped 7 Torch cut 9 Drilled holes 1 Continuous slot 10 Other (specify) 2 Louvered shutter SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft. From ft. to ft. From ft. Fro 10 Livestock pens 14 Abandoned water well What is the nearest source of possible contamination: 4 Lateral lines 5 Cess pool 7 Pit privy 1 Septic tank 11 Fuel storage 15 Oil well/ Gas well 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 2 Sewer lines 3 Watertight sewer lines 6 Seepage pit 9 Feedvard 13 Insecticide storage ..... How many feet? Direction from well? FROM TO PLUGGING INTERVALS LITHOLOGIC LOG FROM Topsoil, sandy clay, dark brown 0 æ Sandy Clay, brown, fine sand 2 13 Silty Clay, some fine sand 13 17 17 Sandy Clay, brown 36 <del>36</del> 40 Sand Survey date: 04/02/15; Datum: NAD83 Latitude: N 37.27544 Longitude: W 97.16849 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)

O3/05/15

and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No.

Under the business name of

OSI Engineering, LLC

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W

Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.