KOLAR Document ID: 1404730

	WELL R			WWC-5		vision of Wat						
		Correction		ge in Well Use		ources App.			Well ID			
1 LOCATION OF WATER WELL: Fraction					ction Numb	1 0						
County: 1/4 1/4 1/4												
						treet or Rural Address where well is located (if unknown, distance and irrection from nearest town or intersection): If at owner's address, check here:						
Address:	u.						needon non nearest town of intersection). If at owner's address, check here.					
Address:												
City:		1	State:	ZIP:								
3 LOCAT		4 DEPTH	OF COM	IPLETED WELL:	f	t. 5 Latit	tude [.]			(decimal degrees)		
	WITH "X" IN SECTION BOX:											
	SECTION BOX: 2) ft. 3) ft., or 4) \Box							WGS 84 🗌 NAI		AD 27		
	WELL'S STATIC WATER LEVEL:						Source for Latitude/Longitude:					
			-yr) -yr)			unit make/model:						
_{NW} -X	NE	Pump test d					WAAS enabled?		0)			
w	E	-	hours				Survey 🔲 Topogra e Mapper:					
			Well w	ft.								
SW	SE		hours	gpm	6 Flow	6 Elevation: ft Cround Level TOC						
		Estimated Y		C 1		6 Elevation:ft. □ Ground Level □ TOC Source: □ Land Survey □ GPS □ Topographic Map						
	S nile	Bore Hole I			<u>50010</u>							
1 mile												
1. Domestic: 5. Dublic Water Supply: well ID 10. Oil Field Water Supply: lease												
	□ Household						11. Test Hole: well ID					
🗌 Lawn a	□ Lawn & Garden 7. □ Aquifer Recharge				well ID			Cased Uncased Geotechnical				
	Livestock 8. Monitoring: well ID						12. Geothermal: how many bores?					
2. 🗌 Irrigati				al Remediation: well II				Loop Horizont				
	3. Feedlot Soil Vapo					b) Open Loop 🗌 Surface Discharge 🔲 Inj. of Water						
4. Industrial Recovery Injection 13. Other (specify):												
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:												
Water well disinfected? Yes No 8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to ft., Diameter in. to ft., Diameter ft.												
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
□ Steel □ Stainless Steel □ Fiberglass □ PVC □ Other (Specify)												
□ Brass □ Galvanized Steel □ Concrete tile □ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
□ Continuous Slot □ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify)												
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From												
GRAVEL PACK INTERVALS: From												
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other												
Grout Intervals: From												
		e contaminati		,		,						
Septic 2			Lateral Line			Livestock P			cide Storage			
Sewer]			Cess Pool	□ Sewage La		Fuel Storag			oned Water			
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well												
Other (Specify) Direction from well? ft.												
10 FROM	TO		ITHOLO		FROM	ТО		HO. LOG (cont.) or		G INTERVALS		
							Ī					
							1					
					Notes:							
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged												
				no-day-year)								
Kansas Wa	ter Well Con	tractor's Lice	ense No	This Wa	ater Well Re	cord was co	omple	ted on (mo-day-ye	ear)			
under the b	usiness name	<u>e of</u>										
KS Departm				ELL OWNER and retain						785-296-3565		
	KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212											