

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Sumner Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 13 Township Number: T 32 S Range Number: R 2 E

Distance and direction from nearest town or city street address of well if located within city? Block 41 Lot 14 in Oxford, Kansas South East corner

2 WATER WELL OWNER: L. F. Schreiner RR#, St. Address, Box #: 120 E Main Oxford City, State, ZIP Code: 67119 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the SW quadrant] 4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 64 ft. Depth(s) Groundwater Encountered 1. 39 ft. 2. 64 ft. 3. 64 ft. WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr Pump test data: Well water was 24 ft. after 1 hours pumping 13 gpm Est. Yield 7.8 gpm Well water was 65 ft. after 13 hours pumping 13 gpm Bore Hole Diameter: 7.8 in. to 6.5 ft., and 6.5 in. to 6.5 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded Blank casing diameter 5 in. to 6.5 ft., Dia. 16 in. to 16 in. weight 16 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 55 ft. to 65 ft. GRAVEL PACK INTERVALS: From 65 ft. to 24 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 24 ft. to 26 ft., From 0 ft. to 1 ft. What is the nearest source of possible contamination: 1 Septic tank 2 Watertight sewer lines 3 Sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Insecticide storage 13 Fertilizer storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	15	Clay			
15	39	Subs sand			
39	65	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) May 10 1989 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 506 This Water Well Record was completed on (mo/day/yr) under the business name of metz water well service by (signature) Dennis metz