mw-1-								
WATER WEI		Form W	WC-5			r Resources App. N		
3	OF WATER WELL:	Fraction		Secti		Township No.		
	abette	SE 4NW 4SE	= 145W 1/4		10	T 32 S		
	Address of Well Location;			Globa	al Positioning	System (GPS) in 5.9.50.40	iformation:	_
from nearest t	town or intersection: If at	owner's address, chec	k here 🔏.	Latiti	ude:	7.070.7	(in decimal d	legrees) E
				Long	itude:Jl.	2034.327	O (in decimal d	legrees)
	114	a 5		Detur	ation:	-40.80	I NAD 27	
2 WATER WELL OWNER: Cansas Hrmy Ammunition Plant RR#, Street Address, Box #: 23318 Park Park Park Park Park Park Datum: WGS 84, NAD 83 Collection Method: GPS unit (Make/Model:							NAD Z'NA	ND RR
RR#, Street A	Address, Box #:		at rant		GPS unit (Mak	ce/Model:)
City, State, Z	IP Code : 2001	0 600V7 500V	_		Digital Map/Ph	ioto, 🔲 Topographi	c Map, 🔀 Land S	Survey
2 LOCATE NE		15, Ks. 67	552	Est. A	ccuracy:	3 m, 3-5 m, 3	$5-15 \text{ m}, \square > 15$	m
3 LOCATE WE WITH AN "X	"IN 4 DEPTH OF	COMPLETED WEL	ı. 19		ft			
SECTION BO							3)	ft
Depth(s) Groundwater Encountered (1)								
Pump test data: Well water wasft. after hours pumping								
EST. YIELDgpm. Well water wasft. after hours pumping								
w E Bore Hole Diameter 8.7.25in. toft., andin. toft.								
WELL WATER TO BE USED AS: □ Public water supply □ Geothermal □ Injection well								
SWSE Domestic								
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted.								
S If yes, mo/day/yr sample was submitted								
·		7-						
5 TYPE OF CASING USED: Steel X PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter								
Casing diamet	er	It., Diameter		1bo /4	II., D	lameter	in. to	π.
Casing height above land surface								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.								
SCREEN-I ERG	ORATED INTERVALS.	From	ft to		ft From		to	······ ft.
GRAV	EL PACK INTERVALS:	From.	ft. to J. 9		ft., From	ft.	to	ft.
		From						
6 GROUT MA	TERIAL: Neat ceme	ent 🔲 Cement grou	t 🛛 Bento	nite [Other	• • • • • • • • • • • • • • • • • • • •		
Grout Intervals:	From 9 ft. to		n	ft. to	ft.,	From	ft. to	ft.
	est source of possible conta							
Septic ta		nes Pit privy	Livestock		Insecticide		er (specify below	<i>i</i>)
Sewer lin	ht sewer lines Seepage p		☐ Fuel storage ☐ Fertilizer s		☐ Abandoned ☐ Oil well/ga			
	n well							
FROM TO	LITHOLOG		FROM	TO		OG (cont.) or PLU		RVALS
0 10	Clay, dark brown,							
	and plastic							
10 19	Thate ever water	d						
	,							
	,							
					Grie	g inal Returne	d to Sandar	
						_	1	1,,,
					101	Correction E	/ate: 1///	.110
7 CONTRA CO	ODIC OD I ANDOMEST	10 Opporato (or c	NI. TO	- 11	157	1 []	1 prom	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) . 10.726 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No								
under the business name of Environmental Priesrity Service. Fire by (signature)								
INSTRUCTIONS:	Use typewriter or ball point pen	. PLEASE PRESS FIRML	Y and PRINT cl	early. Ple	ase fill in blanks	and check the correc	t answers. Send th	ree copies
(white, blue, pink) t	o Kansas Department of Health	and Environment, Bureau	of Water, Geol	ogy Section	on, 1000 SW Jac	ckson St., Suite 420,	Topeka, Kansas 66	6612-1367.
	5522. Send one copy to WAT ov/waterwell/index.html.	ER WELL OWNER and	retain one for	your recor	rds. Include <u>fee</u>	of \$5.00 for each c	onstructed well.	√isit us at
KSA 82a-1212	ovi water well/illuex.illilli.							