## mw-11-A cont nell

WATER WELL RECORD	Form WWC-5	Division of Wate	r Resources App. No	0.	
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township No.	Range Number	
County: Abette	1/2 NW 1/2 SW 1/2 NW/2	11	T 32 S	R 20 BE □W	
Street/Rural Address of Well Location		Global Positioning	i System (GPS) in	formation:	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					
Elevation:					
Scott Rd + 2400 ROAD  Datum: M WGS 84, MAD 83, MAD 27					
2 WATER WELL OWNER: US ARMY Corps of Engineers Collection Method:  RR#, Street Address, Box #: (A) F 1 DTH e-T Collection Method: (Make/Model: Greener Eleck)					
City State 71P Code GO Land Survey   Digital Man/Photo Topographic Man T Land Survey					
2m: 463 Lansas coty Mo 6406 Est. Accuracy: □ <3 m. \$3-5 m. □ 5-15 m. □ >15 m					
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 18	fi.			
SECTION BOX: Depth(s) Groun	CCTION BOX: Depth(s) Groundwater Encountered (1)ft. (2)ft. (3)ft.				
WELL'S STATIC WATER LEVEL IVAft. below land surface measured on mo/day/yr					
Pump test data: Well water was					
W NW NE E EST. YIELD					
WELL WATER TO BE USED AS:   Public water supply   Geothermal   Injection well					
Domestic					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☒ Monitoring well					
S If yes, mo/day/yr sample was submitted					
mile  Water well disinfected?  Yes X No					
5 TYPE OF CASING USED: Steel PVC Other CM					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter					
Casing height above land surface30					
Steel Stainless Steel VC Other (Specify) . CM I. Levil . Screen					
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot Will slot Gauze wrapped Torch cut Drilled holes None (open hole)  Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From ft to ft.  From 7.5 ft to 5.0 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 7.5 ft to 6.5 ft.  From 7.6 ft to 6.5 ft.  GRAVEL PACK INTERVALS: From 7.6 ft. to 6.5 ft.  From 7.6 ft to 6.5 ft.  From 7.6 ft to 6.5 ft.  From 7.6 ft.					
Louvered shutter   Key punched   Wire wrapped   Saw cut   W Other (specify) Court walk   17.5-16					
SCREEN-PERFORATED INTERVALS: From ft. to					
From					
From 2.0 ft to 8.5 ft, From // ft to					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other A Like plus Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.					
Grout Intervals: From					
What is the nearest source of possible con	tamination:	_	_	er (specify below)	
Septic tank Lateral l	nes Pit privy Livestock Sewage lagoon Fuel storage	_		er (specify below)	
☐ Watertight sewer lines ☐ Seepage	pit Feedyard Fertilizer s			***************************************	
Direction from well		from well		CCINIC INTERVALE	
FROM TO LITHOLOG	GIC LOG FROM	TO LITHO LO	JG (cont.) of PLU	GGING INTERVALS	
4' 19' Line Stone					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, are plugged					
under my jurisdiction and was completed on (mo/day/year) 5:6 2015 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No. 5.1. This Water Well Record was completed on (mo/day/year) 5.15.2015					
under the business name of Coscal UNIVY by (signature)					
INSTRUCTIONS Use rypewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367 Felephone 785-296-5522 Send one copy to WATER WELL OWNER and retain one for your recerds. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gcv/waterwel//ndex.html.					
KSA 82a-1212		Check: 🔲 Wh	ite Copy, 🔲 Blu	ie Copy, 🔲 Pink Copy	