## MW-17-A

WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number	
County: Abette	1.5W 1.5W 1. NW1.	// T 32 S R 20 ME []	
Street/Rural Address of Well Location; from nearest town or intersection: If at		Global Positioning System (GPS) information:	
KANSAS Army Amuntion		Latitude: 37.37601 (in decimal degrees Longitude: 75.17354 (in decimal degrees	
Scott Rd + 2400 Ro		Elevation:	
2 WATER WELL OWNER: US AR	my Capp at fix it was	Datum: W WGS 84, NAD 83, NAD 27 Collection Method:	
RR#, Street Address, Box #: City, State, ZIP Code : Got E	I USB OF CHE THERE	GPS unit (Make/Model: . GARMAN E. T.C.X	
City, State, ZIP Code	12 1/ ant M. (18)	Digital Man/Photo. Topographic Man. Land Survey	
2m; 463 Longas Coty Mo 6406 Est. Accuracy: - <3 m. 3-5 m, 5-15 m, >15 m			
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 19	ft.	
SECTION BOX: Depth(s) Ground	dwater Encountered (1)	ft. (2) ft. (3) ft	
N WELL'S STAT	IC WATER LEVEL. W.Af	below land surface measured on mo/day/yr	
Pump test data: Well water was			
W E Bore Hole Diam	neterin. to	ft., andft.	
WELL WATER	TO BE USED AS:   Public wa	ter supply Geothermal Injection well	
Domestic		er supply Dewatering Other (Specify below	
Irrigation	Industrial University of the Control	wn & garden 🔀 Monitoring well	
S If yes, mo	day/yr sample was submitted		
	fected? 🗌 Yes 🕱 No		
5 TYPE OF CASING USED: Steel PVC Other CM.T. Will			
CASING JOINTS: Glued Clar	nped 🔲 Welded Threade	đ	
Casing diameter			
Steel Stainless Steel	·vc 🕤	Other (Specify) CM Tuk!	
Casing height above land surface			
Casing height above land surface 30 in., Weight bs./ft., Wall thickness or gauge No.  YPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel VC Other (Specify) W. T. Well  Brass Galvanized Steel None used (open hole)  CREEN OR PERFORATION OPENINGS ARE:  Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)  CREEN-PERFORATED INTERVALS: From ft. to ft. From 18.5 ft. to ft.  GRAVEL PACK INTERVALS: From 3.5 ft. to ft.			
Continuous stot Mill stot Gauze wrapped Torch cut Drifted holes Twohe (open tiple Source)  Louvered shutter Tkey punched Wire wrapped Saw cut. Sother (specify)			
SCREEN-PERFORATED INTERVALS: From			
From(3.5%, It. 10 It., From It., From It. U It.			
GRAVEL PACK INTERVALS:	From 19.5 ft to 12.9	ft, From /6-0 ft. to 19-0	
6 GROUT MATERIAL: Neat ceme	ent Cement grout Bento	nite BOther A Ide Plus	
Grout Intervals: From ft. to	ft., From	ft. toft., From tt. toft.	
What is the nearest source of possible conta		pens	
Septic tank Lateral lin	es Pit privy  Livestock Sewage lagoon  Fuel storage		
☐ Watertight sewer lines ☐ Seepage p	oit Feedyard Fertilizer s	torage Oil well/gas well	
Direction from well		from well	
FROM TO LITHOLOG	IC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVAL	
14' 19. him Stone			
THE MINES WITH			
7 CONTRACTOR'S OR LANDOWNER	S CERTIFICATION: This wat	er well was 🔀 constructed, 🔲 reconstructed, or 🔲 plugged	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 5.6.305 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No. 54 This Water Well Record was completed on (20/day/year) 18-15			
l Kansas Water Well Contractor's License N	o This Water Well R	ecord was completed on (200 day) veat	
under the business name of			
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., State 420, Topeka, Kansas 66612-1367 Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www.kdhcks.gov/waterwell/index.html			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			