mw-13-Px-Cmt well

WATER WELL RECORD Form WWC-5 Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction Section Number Township No. Range Number
County: Abette 1/2 5w 1/2 5w 1/2 NW1/4 1/ T 32 S R 20 ME W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here
LANSAS Army Amuntion Plant Longitude: 95.19992
Elevation:
A Man II (Out of D)
2 WATER WELL OWNER: US ARMY Corps of Engineers Collection Method: RR#, Street Address, Box #: Gol E 2714 31
City State 7IP Code GO LE GO L
2m; 463 Konsas coty Mo 6406 Est. Accuracy: - <3 m. 3-5 m 5-15 m>15 m
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL ft.
1 SECTION DOX: Debut(2) Globaldwatci Ellowatteted (1)
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr
Pump test data: Well water wasft. after
W S Bore Hole Diameter
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
□ Irrigation □ Industrial □ Domestic-lawn & garden ☒ Monitoring well
S If yes, mo/day/yr sample was submitted
mile Water well disinfected? Yes No
5 TYPE OF CASING USED: Steel PVC Other CMI Let
! CASING JOINTS:Glued Clamped Welded
Casing diameter a. in. to 90 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface30
Steel Stainless Steel PVC POther (Specify) WW WILL SCIEBLE
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)
Continuous slot fill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)
SCREEN-PERFORATED INTERVALS: From
From $\mathcal{G} \cdot \mathcal{O}$ ft to $\mathcal{S} \cdot \mathcal{S}$ ft. From $\mathcal{G} \cdot \mathcal{G}$ ft. to $\mathcal{G} \cdot \mathcal{S}$ ft. to $\mathcal{G} \cdot \mathcal{S}$
GRAVEL PACK INTERVALS: From 2.0 ft. to 3.5 ft., From 41.5 ft. to 6.0 ft. From 7.5 ft. to 9.0 ft., From 41.5 ft. to .22 ft.
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other A. Isle Plag
Grout Intervals: From
What is the nearest source of possible contamination:
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well
Direction from well
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 3' Svi 3' 40 Lin Stune
3º 30 Lin Stune
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged
under my jurisdiction and was completed on (mo/day/year) 56-75 and this record is true to the best of my knowledge and belief
Kansas Water Well Contractor's License No. 15.2.7 This Water Well Record was completed on Landday/year) . 5.2.48
under the business name of LASCARL MANUAL DE by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the contect answers. Send three copic (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-136
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us
http://www.kdhcks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Cop