


1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NW 1/4 Section Number 6 Township Number T 32 S Range Number R 21 EW

Distance and direction from nearest town or city street address of well if located within city?
 2 Miles East of Parsons, KS on Hwy 160 Well No. 20-3

2 WATER WELL OWNER: U. S. Army
 RR#, St. Address, Box # : Kansas Army Ammunition Plant Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Parsons, KS Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL 20.8 ft. ELEVATION: 854.01 @ top of casing.
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 999 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was . ft. after . hours pumping . gpm
 Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter . in. to . ft., and . in. to . ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes . No . If yes, mo/day/yr sample was submitted .
 Water Well Disinfected? Yes . No .

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued . Clamped . Welded . Threaded .
 Blank casing diameter . 2 . in. to 10.2 . ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface . 2 . Ft . in., weight . lbs./ft. Wall thickness or gauge No. Sch 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify) Factory Slot
 SCREEN-PERFORATED INTERVALS: From 10.2 . ft. to 20.2 . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 6.7 . ft. to 20.8 . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From (.3) 2.8 . ft. to 6.7 . ft., From (2) 0.0 . ft. to 2.8 . ft., From . ft. to . ft.
 What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Unknown

DIRECTION FROM WELL?		LITHOLOGIC LOG		PLUGGING INTERVALS	
FROM	TO	FROM	TO	FROM	TO
0.0	6.3		Clay		
6.3	8.5		Claystone, Weathered Gray Orange		
8.5	10.0		Claystone, Weathered Yellow Brown		
10.0	21.8		Limestone		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/7/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 458 This Water Well Record was completed on (mo/day/yr) 1-29-93 under the business name of The Winnek Co. Inc. by (signature) Dale Ann Bowlin

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4