				R WELL RECORD	Form WM		32a-1212		
_	ON OF WAT	ER WELL:	Fraction	4 0 9	SE	Section Numb	· · ·	_	Range Number
County:	nd direction	trom pearest to		ddress of well if lo		27	T 36	L s] R 4 (F)W
Distance a	2000 I	iquitex	Lane, Wi	nfield,Ks	• within ci	.y ?			
2 WATER	WELL OW	NEM:	lmark Ca						
RR#, St. A	Address, Box	• " •	XX liquites				Board of	Agriculture,	Division of Water Resources
City, State,	ZIP Code	$\omega_{\mathbf{u}}$	ifield, Ks.			Application Number:			
LOCATE	WELL'S LO	OCATION WITH	4 DEPTH OF C	OMPLETED WELL	20'	ft. ELE	VATION:		
」 AN "X"	IN SECTION	BOX:	Depth(s) Ground	water Encountered	1.151		t. 2	ft. 3	3
ī [1	<u> </u>							3-31-97
I 1	1								umping gpm
-	- NW	NE						•	umping gpm
	- i		Bore Hole Diame	eter 8/27. in	. to 20		t., and	in	n. to
. <u>*</u> w -		1	WELL WATER	TO BE USED AS:	5 Public v	water supply	8 Air conditioni	ng 11	Injection well
-	1		1 Domestic	3 Feedlot	6 Oil field	water supply	9 Dewatering	12	Other (Specify below)
-	- 2M	3:	2 Irrigation	4 Industrial					
1 1	- 1		Was a chemical/	bacteriological sam	ple submitted t	o Department?	YesNo	; If yes	s, mo/day/yr sample was sub
	S		mitted				Water Well Disinfed	ted? Yes	(No)
TYPE C	F BLANK C	ASING USED:		5 Wrought iron	8 Cc	ncrete tile	CASING J	OINTS: Glue	d Clamped
1 Ste	el	3 RMP (SI	R)	6 Asbestos-Cem	ent 9 Ot	her (specify be	elow)	Weld	ded
2 PV		4 ABS	1	7 Fiberglass					aded X
				ft., Dia	in	. to	ft., Dia		in. to $.SDR13$ ft.
Casing hei	ght above la	ind surface.FU	white	.in., weight		<u></u>	s./ft. Wall thicknes	s or gauge N	lo SCh · 40 · · · · ·
		R PERFORATION			Z	PVC	10 A	sbestos-cem	ent
1 Ste	el	3 Stainless	s steel	5 Fiberglass	8	RMP (SR)	11 0	ther (specify))
2 Bra	ass	4 Galvaniz	zed steel	6 Concrete tile	9	ABS	12 N	one used (or	pen hole)
SCREEN C	OR PERFOR	RATION OPENIN	IGS ARE:	5 G	auzed wrappe	d	8 Saw cut		11 None (open hole)
1 Co	ntinuous slo	t 3 M	lill slot	6 V	Vire wrapped		9 Drilled hole:	S	
2 Lou	uvered shutt	er 4 Ke	ey punched	- '	orch cut,		` •		
SCREEN-F	PERFORATE	D INTERVALS:	FromZ						toft.
			From						toft.
G	RAVEL PAG	CK INTERVALS:	From Z	O ft. 1	to %	ft., F	rom	ft. 1	toft.
			From	ft.			rom	ft.	to ft.
GROUT	MATERIAL	: 1 Neat o	cement	Cement grout ft., From	سارر نالار نالار	entonite	4 Other		ft. toft. Abandoned water well
Grout Inter	vals: Fron	n	\$ to . Y . Q	ft., From	4.W	ft. to.	ft., From	· · · · · · · · · ·	ft. to
		•			_	\sim		. / /	
							el storage/Cher		
							Other (specify below)		
	_	er lines 6 Seep	• .	9 Feedyar	ď		secticide storage	, , , , , , , , ,	
FROM I	rom well? A	lauthwest	LITHOLOGIC	106	FROM		many feet? 200	PLUGGING I	INTEDVALC
0	•50	Concret			FRUI	, 10		Loading	IIVI E I IVALO
				La			<u> </u>		
.50	4			to gray bi	rn qray,				
1	9	•	no odor.						
4	9			y w/ oxide		ng			
				cretions,	ary,				
	1 5 50		no odor.				4		The second state of the Asia Asia Asia Asia Asia Asia Asia Asia
9	15.50			silty cla					
1		Tan bra	ey silt,	soft, mos sandy sil	LSt.				and the second of the second o
15.50	20			pebbles of					
			no odor						
		10,900,	110 Odol	•					
							ENAK	4.6. 5	Taylor
							F.H. UN	~ uch vo	- rugue
									11/A 17/14A
7 601.75	ACTORIO C	NO I ANDOMATIC	DIS CERTIFICATI	ION. This water	all 1400 /46	etrusted (70) =		nlugged	dor my hydrodictics and
		year) 3:27-		ion; inis water we	en was (ii) con				der my jurisdiction and was
		•	539	Th:- \A/-4	or Woll Doors		ecord is true to the led on (m <u>o/</u> day/yr)	4-2-Q	nowledge and belief. Kansas 7
		s License No		ntal Drill				12.0	ha 1)
							nature pm		
of Health	TIONS: Use type hand Environment	pewriter or ball point ent, Bureau of Water,	pen. PLEASE PRESS F Topeka, Kansas 6662	o-0001. Telephone: 913-	iy. Please till in bla 296-5545. Send or	inks, underline or c le to WATER WELL	ircle the correct answers . OWNER and retain one	for your record	copies to Kansas Department s.