		RECORD		VC-5			r Resources: Ap	·	
1 LOCA	TION OF	WATER WELL: Fra	SE & NE	. sw					Range Number
Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)									
located within city? 1318 Main St. Winfield, KS Latitude: N 37.23532° Longitude: W 96.99645°									
2 WATI	CD WELL	OWNER: QuikTrip	Corneration	Longi	Elevation: RIM: 1128.09 TOC: 1127.82				
DD# 6		D 4 . 4705 C 120	Oth To Asso		Datur	n.	above mean s	ea level	7.02
City S	state. ZIP C	nde : Tulsa OK	74134-7008		Data	n. Collec	tion Method:	legal survey	
City. State, ZIP Code : Tulsa. OK 74134-7008 Data Collection Method: legal survey 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 23 ft.									
LOCA					MW	/3			
	I AN "X" I	N Depth(s) Groundwa	ater Encounter	red 1				ft. 3	ft.
	ION BOX:	WELL'S STATIC	WATER LEV	EL 17.4	ft. belo	w land	surface meas	ured on mo/d	lay/yr 10/7/09
5201	N								
N Pump test data: Well water was ft. after hours pumping gp Est. Yield gpm: Well water was ft. after hours pumping gp WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									ing gpm
									niection well
	W E Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well								
W									
- sw - sE - Z migation 4 madshall / Boniestic (lawn & garden)									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs									
Sample was submitted Water Well Disinfected? Yes No X									
THE OF CASING HOPE. 5 When the Land Of Comments tills CASING HOPITS, Clark Clark									
5 TYPE	OF CASI	NG USED: 5 WI	ougni iron	8 00	har (specif	. hala	CASING JOI	NIS: Glued	Clamped
1 Ste	eel	3 RMP (SK) 6 ASI	bestos-Cemen	9 01	ner (specif	y belo	w)	Weide	U 1-1 17
$\left[\begin{array}{c} (2)^{\text{PV}} \end{array}\right]$	·	4 ABS / F10	ergiass				A D:-	Inread	led X
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia in. to ft.									
Casing height below land surface 0.27 ft., Weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Steinless steel 5. Fibergless (7) PVC 9. ABS 11. Other (checify)									
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)									
1 Continuous slot (3) Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)									
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 11 ft. to 23 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
SCREEN-	-PERFORA	TED INTERVALS: F	From 1	3 ft. t	0 23		ft. From	ft. t	o ft.
From ft. to ft. From ft. to									οπ.
GRAVEL PACK INTERVALS: From 11 ft. to 23 ft. From ft. to									οπ.
From ft. to ft. From ft. to ft.									
6 GROU	J T MATE I	RIAL: 1 Neat cement	: 2 Cement s	grout (3)	Bentonite	(4)	Other Concre	te: 0-2 ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-2 ft. Grout Intervals From 2 ft. to 11 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
	tic tank	4 Lateral lines			vestock pe		3 Insecticide S		16 Other (specify
	er lines		8 Sewage lag				4 Abandoned		below)
		er lines 6 Seepage pit	9 Feedyard				5 Oil well/ gas	s well	
Direction	from well?	NW		How 1	many feet?	~65			
FROM	TO	LITHOL	OGIC LOG		FROM	TO	PLU	IGGING INT	ERVALS
0	0.5	Grass, topsoil							
0.5	3	Silty clay, brown, fine to co							
3	7	Silty clay, brown, moderate							
7	8	Clay, red brown, some silt,							
8 15	15 20	Silty clay, red brown, mode Silty clay, olive gray, mode				<u> </u>			
20	23	Silty clay, olive gray, fine to							
	20	plasticity, wet	Coarse sand, Inc	, aci atc					
							Flushmount	waiver from	1 BOW
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged									
under my jurisdiction and was completed on (mo/day/year) 10/5/09 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed op (pro/day/year) 11/19/09 under the business name of Larsen & Associates, Inc. by (signature)									
1					ignature) _				
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send to WATER WELL OWNER and retain one for									
your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.									