


1 LOCATION OF WATER WELL: Fraction NE SW Section Number 28 Township Number 32 Range Number 4
 County: Cowley

Distance and direction from nearest town or city street address of well if located within city?
519 E 9th; Winfield, KS

2 WATER WELL OWNER: R.L. Baker
 RR#, St. Address, Box #: 53 West Bourough Rd. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Wellington, KS 67152 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1.13' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 12.98' ft. below land surface measured on mo/day/yr 4-14-98
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 1/2" in. to 20' ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No X.....; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
 Blank casing diameter: 2.875 in. to 10' ft., Dia. in. to ft., Dia. in. to SDR 13 ft.
 Casing height above land surface: Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SCH 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft., From ft. to ft. ft. to ft.
 GRAVEL PACK INTERVALS: From 20' ft. to 8' ft., From ft. to ft. ft. to ft.

6 GROUT MATERIAL:
 Grout Intervals: From 8' ft. to 3' ft. From 3' ft. to 0' ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage tower 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? Southeast How many feet? 210'

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|----|---|------|----|--------------------|
| 0 | 4 | Grass-Black organic rich clayey top soil moist, roots, no odor | | | |
| 4 | 13 | Med clay-gray brn clay grading to clayey silt, moist no odor oxide staining no odor | | | |
| 13 | 17 | Red brn silty clay, moist to wet, no odor med plasticity | | | |
| 17 | 20 | Brn gravelly clay wet, no odor Ls.Rx. qtz pebbles, no odor, firm | | | |
| | | | | | |
| | | | | | |
| | | | | | |

F.H. OK'd by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-14-98 539 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. JB Environmental This Water Well Record was completed on (mo/day/yr) 4-15-98 under the business name of JB Environmental by (signature) James Baker

OFFICE USE ONLY
T
R
SEC