


1) LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 30 Township Number T 32 S Range Number R 4E **EW**
 County: Cowley

Distance and direction from nearest town or city street address of well if located within city?
South 1/2 / lots 12345 NORTH OF HIGHWAY, BLOCK 3, Walch Tracts, a subdivision

2) WATER WELL OWNER: Roy A. Wogoman
 RR#, St. Address, Box #: Rt. # 2 Box 130 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Winfield, Kansas 67156 Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4) DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: Unk
 Depth(s) Groundwater Encountered 1.40 ft. 2 ft. 3 ft. ft.
 WELL'S STATIC WATER LEVEL 3.2 ft. below land surface measured on mo/day/yr 11/27/89
 Pump test data: Well water was 38 ft. after 3 hours pumping 12/15 gpm
 Est. Yield 20/40 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter .8 in. to t.d. ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 (1 Domestic) 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No X No X If yes, mo/day/yr sample was submitted

5) TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped ft.
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ft.
 (2 PVC) 4 ABS 7 Fiberglass Threaded ft.
 Blank casing diameter 5 in. to t.d. ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 20 in., weight 160 psi lbs./ft. Wall thickness or gauge No. sdr26
 TYPE OF SCREEN OR PERFORATION MATERIAL: (7 PVC) 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ft.
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot (3 Mill slot) 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 68 ft. to 75 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From =24 ft. to t.d. ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6) GROUT MATERIAL: (1 Neat cement) 2 Cement grout 3 Bentonite 4 Other ft.
 Grout Intervals: From -4 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 (1 Septic tank) 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage ft.

Direction from well? Southeast How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Soil			
3	5	lt. grn. sh.			
5	10	" " "			
10	15	Grn. Gry. sh			
15	20	" " " shelly			
20	25	blu lm./ chert nodules			
25	40	yellow lm.			
40	50	blu lm/sh (med)			
50	55	sft. blu sh			
55	60	lt grn sh sft			
60	65	" " " "			
65	70	red bed			
70	75	lt blu sh			
75	t.d.				

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/27/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171 This Water Well Record was completed on (mo/day/yr) 12/15/89
 under the business name of G & S Drilling by (signature) [Signature]
 INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one to your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4