


1 LOCATION OF WATER WELL: County: Cowley Fraction: NE 1/4 SW 1/4 NW 1/4 Section Number: 35 Township Number: T 32 S Range Number: R 4-EW
 Distance and direction from nearest town or city street address of well if located within city?
1/2 MI EAST ON 19TH ST. 1/2 SOUTH WINFIELD

2 WATER WELL OWNER: VIC VAUGHAN Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 1506 MILLINGTON Application Number: N/A
 City, State, ZIP Code: WINFIELD KS 67156

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: UNK
 Depth(s) Groundwater Encountered 1. 20/22 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 21.5 ft. below land surface measured on mo/day/yr 9-25-88
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 1-1.5 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 in. to T.D. ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped
 Blank casing diameter 5 in. to T.D. ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 7.5 ft. to 80 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From -19 ft. to T.D. ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From -5 ft. to 19 ft., From ft. to ft.
 What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) CREEK BED

Direction from well? NORTH How many feet? 75

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	23	TOP SOIL / RED CLAY			
23	30	CLAY GRAVEL			
30	60	CHTY LM / SH STRS			
60	68	RED / GRN SH SOFT			
68	80	WHT / GRY LM HARD			
80	T.D.				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171 This Water Well Record was completed on (mo/day/yr) 11-10-88 under the business name of G & S DELG by (signature) Vic Vaughan

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4