


1 LOCATION OF WATER WELL: County: Chautauqua Fraction: SE 1/4 SW 1/4 SE 1/4 Section Number: 10 Township Number: T 33 S Range Number: R 12 E/W

Distance and direction from nearest town or city street address of well if located within city?
4 miles North of Sedan + 6 miles West EAST

2 WATER WELL OWNER: Rod Moore
 RR#, St. Address, Box #: Box 167, Rt. Henderson, Tex 75652
 City, State, ZIP Code: Box 167, Rt. Henderson, Tex 75652
 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 175 ft. ELEVATION: 125 ft.

Depth(s) Groundwater Encountered 1. 125 ft. 2. 68 ft. 3. March 25, 86
 WELL'S STATIC WATER LEVEL 68 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 1/3 gpm: Well water was 8 in. to 110 ft., and 6 in. to 175 ft.

WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 6 in. to 19 ft., Dia. 14 in. to SDR 26 ft., Dia. 14 in. to SDR 26 ft., Dia. 14 in. to SDR 26 ft.
 Casing height above land surface 14 in., weight 14 lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 4 ft. to 19 ft., From 19 ft. to 175 ft., From 175 ft. to 175 ft.
 GRAVEL PACK INTERVALS: From 4 ft. to 19 ft., From 19 ft. to 175 ft., From 175 ft. to 175 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4 ft. to 19 ft., From 19 ft. to 175 ft., From 175 ft. to 175 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Nothing
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Clay base soil			
3	10	Lime			
10	125	Gray Shale			
125	125	Thin lime (water)			
125	130	black Shale			
130	155	Gray Shale			
155	173	Lime			
173	175	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) March 25, 1986 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 393 This Water Well Record was completed on (mo/day/yr) April 8, 1986 under the business name of Country Water by (signature) Ray Weber

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4