WATER WELL RECORD	Form WV	VC-5	Division of Wa	er Resources App. No).
1 LOCATION OF WATER WELL:	Fraction				Range Number
County: Labette	SW 1/4 SW 1/4 SW		Clahal Pagitiania	T 33 S g	R 19 ZE W
Street/Rural Address of Well Location; if from nearest town or intersection: If at of			Latitude:3.		(in decimal degrees)
Bailey's Corner #2			Longitude: 95, 28557 (in decimal degrees)		
1107 East 4th Street, Altamont, KS 67330			Elevation: 904.33		
2 WATER WELL OWNER: Sunshine Fuel, LLC			Datum: WGS 84, V NAD 83, NAD 27 Collection Method:		
RR#, Street Address, Box #: 2751 SW Barnes Avenue			GPS unit (Make/Model:)		
City, State, ZIP Code : Independence, KS 67301			☐ Digital Map/Photo, ☐ Topographic Map, ✔ Land Survey		
Est, Accuracy: ✓ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 19.5 ft.					
SECTION BOX: Depth(s) Groundwater Encountered (1)					
N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr.0-23-14					
Pump test data: Well water was N/A ft. after N/A hours pumping N/A gpm EST. YIELD N/A gpm. Well water was N/A ft. after N/A hours pumping N/A gpm					
10^{-10} 10^{-10}					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)					
Domestic-lawn & garden V Monitoring Well MVV.9					
Was a chemical/bacteriological sample submitted to Department? Yes V No					
s If yes, mo/day/yr sample was submitted. N/A					
which well disinfected: 1es					
5 TYPE OF CASING USED: Steel V PVC Other					
Casing diameter 2. in. to .4.5. ft., Diameter N/A in. to N/A ft.					
Casing height above land surface 0 in., Weight N/A lbs./ft., Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
Steel Stainless Steel PVC Other (Specify)					
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 4.5 ft. to 19.5 ft., From N/A ft.					
SCREEN-PERFORATED INTERVALS: From .4.9 ft. to .19.5 ft., From .10/A ft. to .10/A ft.					
GRAVEL PACK INTERVALS: From 4 ft. to 19.5 ft., From N/A ft. to N/A ft.					
From N/A ft to N/A ft From N/A ft to N/A ft					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Concrete 0-2 feet Grout Intervals: From .2					
Grout Intervals: From .2 ft. to .4 ft., From .N/A ft. to .N/A ft., From .N/A ft. to .N/A ft.					
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well					
Direction from well South.	molet-		from well 86		JGGING INTERVALS
FROM TO LITHOLOG		FROM	TO LITHO.	LOG (cont.) or PLC	JOUINO INTERVALS
0 0.5 dk brn silty clay firm do					
19.5 Auger refusal on sand		1			
7 Jugor Tolagar off Sand	3.011.0				
	COMMAND 18				
					and the state of t
		 			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) 6/23/2014 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 759 This Water Well Record was completed in (mo/day) year) 7/13/2014 under the business name of RAZEK Environmental LLC					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to					
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html .					
	mp //www.kaneks.go	KUMATET MEHUHU	ua-HHHH		