WATE		RECORD	Form WWC-5		Division of Wate	er Resources; App. No.	46,452
	ATION O	F WATER WELL: ey	Fraction 1/4 NC 1/4 N	W 1/4	Section Number 32	Township Number T 33 S	Range Number R 3 (E) W
Distar withir	nce and dire	ction from nearest town or city str proximately 1 1/4 miles east	eet address of well if loca	ited		ng Systems (decimal deg 139655	
RR#	, St. Addre	L OWNER: Kendall E. Rich			Elevation: Unknown Datum: NAD 83		
City, State, ZIP Code : Arkansas City, KS 67005 Data Collection Method: WAAS GPS Unit 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 46.5 ft.							
W LOC WITI SEC'	ATION H AN ''X' TION BO NNESE S	Depth(s) Groundwater WELL'S STATIC WA Pump test data Est. Yield Unknown gpm WELL WATER TO B 1 Domestic 3 2 Irrigation 4 Was a chemical/bacter Sample was submitted	Encountered (1) TER LEVEL 8 I: Well water was Not in: Well water was E USED AS: 5 Public Feedlot 6 Oil field industrial 7 Domesticological sample submissions.	ft checke ic water I water s ic (lawn itted to Water	ft. (2) below land surfa d ft. after ft. after supply 8 Air upply 9 Der & garden) 10 Mo Department? Yes well disinfected?	hours pumping	gpm
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded							
Blank casing diameter 12 in. to 31 ft., Diameter in. to ft. Casing height above land surface 30 in., weight 10.31 lbs./ft. Wall thickness or gauge No420							
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel (3) Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)							
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: (1) Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify)							
SCREEN-PERFORATED INTERVALS: From 31 ft. to 44 ft., From ft. to ft.							
SCREEN-PERFORATED INTERVALS: From 31 ft. to 44 ft., From ft. to From ft. to ft., From ft. to GRAVEL PACK INTERVALS: From From 21 ft. to 45 ft., From ft. to From ft. to ft., From ft. to							ft. ft.
6 GROUT MATERIAL: 1 Neat Cement (2) Cement grout 3 Bentonite (4) Other Bentonite Holeplug							
Grout Intervals: From 0 ft. to 19 ft., From ft. to ft., From 19 ft. to 21 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage (16) Other (specify							
1 Septi 2 Sewe	c tank er lines	5 Cess pool 8 S	Sewage lagoon 11	Fuel sto	rage 14 Ab	andoned water well	16) Other (specify below) None known
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well None known Direction from well? How many feet?							
FROM	TO	LITHOLOGIC LOC	3	FROM	TO	PLUGGING INTE	RVALS
3	3 5	Topsoil Clay, brown		 			
5	38	Sand and gravel, fine, med	dium				
38	40	Sand, fine	P		ļ		
40 44	44 45	Sand and gravel, fine, med Shale	lium, coarse		<u> </u>		
44	45	Silale					
		<u> </u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-6-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on mo/day/year) 6 13-06 Under the business name of Clarke Well & Equipment, Inc. by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone							
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							