WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Location of well: | County Cowley | Fraction NW | NE 1/4 N | W.J | Section | number | Township number Range number 4 | |
|--|-------------------------------------|--|-------------|---------|------------|--|---|-----|
| 2. Distance and direc | ction from nearest town or city: | + miles | south | | ner of wel | | T (S) R (E)W Ronal Heffron | - |
| And 1/4 I Street address of well | mi. west, of Winfi | eld, Kar | nsas | R.R. or | |] | Route 3 | |
| 4. Locate with "X" i | | Sketch map: F | | City, s | tate, zip | code: [| Winfield, Kansas 67156 F Bore hole dia. 10 in. Completion date 9/15/ | 78 |
| , N | | | | 5 | Ut. | 714 | Well depth ft | Ĭ |
| W SW SE E SW SE SE SW SE SE SW SE SW SE SW SE SW | | | | ا في | Storage | | 7. X Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary | |
| | | | | 200 | | | 8. Use: X Domestic Public supply Industry | |
| | | | | y we | | | Irrigation Air conditioning Stock Lawn Oil field water Other | |
| | | | | 5 | | | 9. Caring Above of below Threaded Welded Surface 24 in. | 1 |
| 5 | | | | _ | 6 | | RMPIbs./ft. | l |
| 5. Type and color of material | | | | From | То | Dia. 5 in. to 75 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. Schedule | 40 | |
| | | | | | | | 10. Screen: Manufacturer's name | |
| Top Soil | | , | | | 0 | 5 | Type PVC Dia. 5'' (Slot/gauze 1/16 Length 10 ft | |
| Clay | | | | | _5_ | 10 | Set between65ft. and75ft. | |
| Lime | | | | | 10 | 15 | ft. andft. Gravel pack?Size range of material5/8" | |
| Lime Shale | | | | 15 | 30 | 11. Static water level: 9/15/48. | | |
| Blue Shale | | | | 30 | 50 | 12. Pumping level below land surfaces: Daller tel | st | |
| Red Bed | | | | | 50 | 55 | ft. after hrs. pumping g.p.m ft. after hrs. pumping g.p.m. | |
| Blue Shale | | | | 55 | 60 | Estimated maximum yield | | |
| T.J | | | | | 60 | 6 F | Yes _X No Date | |
| Lime | _ | | | | 60 | 65 | 14. Well head completion: Pitless adapter | |
| Blue Shale | 9 | | | | 65 | 75 | 15. Well grouted? | ł |
| | | | | | | | Depth: From <u>0</u> ft. to <u>17</u> ft. | |
| | | | | | | | 16. Negrest source of possible contamination: fuel tar | hks |
| | | -1916 | ··· | | | | Well disinfected upon completion? X Yes No | 1 |
| | | ************************************** | | | | | Manufacturer's name | " |
| | | | | | | | Model number HP Volts Length of drop pipe ft. capacity g.p.m. | × |
| | | | | | | | Type: Submersible Turbine | |
| (Use a second sheet if needed) | | | | | | Jet Reciprocating Other | ا يا | |
| 18. Elevation: 19. Remarks: | | | | | | | 20. Water well contractor's certification: | " |
| unknown Concrete Slab to be installed by | | | | | | | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. | 3 |
| customer at surface of ground. He knows this is a regulation. | | | | | | | Ronal Heffron Drilling #113 | 1 2 |
| X Slope | Q 0 | 11 1 | P | | | | Business norm Winfield, Kansas 67156. Address | 1/2 |
| Upland Valley | Vonal | reff | son | , | | | Signed Authorized representative Date | 2 |
| orward the white, blue | e and pink copies to the Department | of Health and | Environment | | | | Form WWC-5 | |