


1 LOCATION OF WATER WELL: County: Chautauque Fraction: SE 1/4 NE 1/4 SE 1/4 Section Number: 22 Township Number: T 34 S Range Number: R 10 EW

Distance and direction from nearest town or city street address of well if located within city?
10 Miles S.W. of Sedan Ka.

2 WATER WELL OWNER: Billie C. Potter
 RR#, St. Address, Box #: 777 N. Silver Springs #913
 City, State, ZIP Code: Wichita, Ks. 67212
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 199 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1. 220-267 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 215 ft. below land surface measured on mo/day/yr 11-20-84
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 3 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 in. to 199 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded.....
 Blank casing diameter: 1 1/2 in. to 223 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 16 in., weight lbs./ft. Wall thickness or gauge No. 5ch 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 12 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 198 ft. to 223 ft., From 0 ft. to 17 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 110'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Soil Black	184	206	Shale Redd
3	14	lime Shells-White	206	220	shale blue-sticky
14	16	Shale Blue	220	279	sand-gray-coarse 1/2
16	17	lime Blue	279	252	sand-fine-White-Dry
17	21	Shale Blue	252	267	sand-coarse 1/2 GPM
21	38	lime White	267	286	Shale Gray
38	40	Shale Black	286	299	lime-White
40	41	lime Dark			
41	48	Shale Gray			
48	69	Shale Red			
69	71	lime Dark			
71	99	Shale Gray			
99	117	lime Brown			
117	124	Shale Blue			
124	184	Shale Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 11-23-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. HHRA This Water Well Record was completed on (mo/day/yr) 11-24-84 under the business name of Charles B. Darnall by (signature) C. B. Darnall

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4