


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 3 Township Number T 34 S Range Number R 11 EW  
 County: Chautauqua  
 Distance and direction from nearest town or city street address of well if located within city?  
221 W. Main, Sedan, Ks.

2 WATER WELL OWNER: Richard Blake  
 RR#, St. Address, Box #: P.O. Drawer J Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Sedan, Ks. 67361 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 35' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 28' ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 27.9" ft. below land surface measured on mo/day/yr 4-3-94  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 8 1/2" in. to 35' ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded X  
 Blank casing diameter: 23.75 in. to 20' ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface: flush in., weight lbs./ft. Wall thickness or gauge No. SDR 13  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement SCH 40  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 35' ft. to 20' ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 35' ft. to 17' ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout intervals: From 17' ft. to 4' ft., From 4' ft. to 0' ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage Fuel 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage  
 Direction from well? South How many feet? 80'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.75	Grass-dk. med. silty sandy soil, moist, earthy odor.			
1.75	5	Yellow-hard-sandstone, iron stained, dry.			
5	7.75	Pale green sandstone layer w/ slight odor.			
7.75	20	Red brn -yellow sandstone, slight odor. Hard, intermittent hard to med. layers. Mod odor at 20'			
20	35	Mod. odor. Wet at 28' - yellow sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-3-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 4-16-94 under the business name of JB Environmental Drilling by (signature) James Biebel

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4