


1 LOCATION OF WATER WELL: County: Chautauque Fraction: NE 1/4 SW 1/4 NE 1/4 Section Number: H Township Number: T 34 S Range Number: R 12 E

Distance and direction from nearest town or city street address of well if located within city? 3 Miles North of Perry, KS

2 WATER WELL OWNER: Rick Reeves RR#, St. Address, Box #: RT 2 Box 65A City, State, ZIP Code: Sedan, KS 67361 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 109 ft. ELEVATION: 72-74 ft. WELL'S STATIC WATER LEVEL: 50 ft. below land surface measured on mo/day/yr 12-28-86 Pump test data: Well water was 12 gpm: Well water was 109 ft. after 12-28-86 hours pumping 12 gpm Bore Hole Diameter: 10 in. to 109 ft., and 109 in. to 109 ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Observation well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded Blank casing diameter: 6.9 in. to 6.9 ft., Dia. 6.9 in. to 6.9 ft., Dia. 6.9 in. to 6.9 ft., Dia. Casing height above land surface: 54 in., weight 40 lbs./ft. Wall thickness or gauge No. 54 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 6.9 ft. to 6.9 ft., From 3 ft. to 6.5 ft., From 6.5 ft. to 6.5 ft. GRAVEL PACK INTERVALS: From 6.9 ft. to 6.9 ft., From 3 ft. to 6.5 ft., From 6.5 ft. to 6.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 6.9 ft. to 6.9 ft., From 3 ft. to 6.5 ft., From 6.5 ft. to 6.5 ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? North How many feet? 55'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	31	Clay Yellow			
31	34	Shale Dark			
34	37	Shale Gray			
37	41	Shale Blue			
41	43	Lime Brown			
43	63	Shale Blue			
63	70	Shale Blue			
70	71	Lime Gray			
71	73	Sand Gray			
73	109	Shale Sandy-Gray			
		TD 109			
		1/4 G.P.M. 71-73			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-30-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 442 This Water Well Record was completed on (mo/day/yr) 12-30-86 under the business name of _____ by (signature) Charles O. Dornell