GSI Job No. 077232 RMW-128A WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 1 LOCATION OF WATER WELL: Fraction Township Number Range Number Section Number SW 1/4 16 County: Montgomery NW 1/4 SE 25 34 Ε Distance and direction from nearest town or city street address of well if located within city? 400 N. Linden, Coffeyville 2 WATER WELL OWNER: Coffeyville Resources Refining and Marketing, LLC RR#, St. Address, Box # : 400 N. Linden St. Board of Agriculture, Division of Water Resources : Coffeyville, KS 67337 City, State, ZIP Code Application Number: 3 LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 25 ft. ELEVATION: 717.71 (TOC) AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 12.5 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 14.71 ft. below land surface measured on mo/day/yr 08/22/07 -- NW ---Pump test data: Well water was _____ ft. after ____ hours pumping _____ gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8.25 in. to 25 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) W X - SE -2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well S Was a chemical/bacteriological sample submitted to Department? Yes ______No X ___ If yes, mo/day/yr sample was Water Well Disinfected? Yes No X submitted 5 TYPE OF BLANK CASING USED: 5 Wrought Iron CASING JOINTS: Glued Clamped 8 Concrete tile 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 4 ABS Threaded 7 Fiberglass Blank casing diameter 2 in. to 15 ft., Dia in. to ft., Dia in. to ft. Dia in. to 7 PVC 10 Asbestos-cement TYPE OF SCREEN OR PERFORATION MATERIAL: 11 Other (specify) 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 4 Galvanized steel 9 ABS 12 None used (open hole) 6 Concrete tile 8 Saw cut SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 11 None (open hole) 6 Wire wrapped 3 Mill slot 1 Continuous slot 9 Drilled holes 4 Key punched 2 Louvered shutter 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft. From ft. to ft. GRAVEL PACK INTERVALS: ft. to ft. From From 1 Neat cement 2 Cement grout 4 Other Concrete 6 GROUT MATERIAL: 3 Bentonite Grout Intervals From 13 ft. to 2.5 ft. From 2.5 ft. to 0 ft. From ft. to ft. 14 Abandoned water well What is the nearest source of possible contamination: 10 Livestock pens 1 Septic tank 15 Oil well/ Gas well 4 Lateral lines 7 Pit privy 11 Fuel storage 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? LITHOLOGIC LOG PLUGGING INTERVALS FROM CODE FROM Clay, dark brown to brown to gray, silty, with some fine sand from 12.5 to 25 23 feet

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

Geotechnical Services Inc. by (signature)

completed on (mo/day/yr) 09/12/07

Water Well Contractor's License No.

and this record is true to the best of my knowledge and belief. Kansas

This Water Well Record was completed on (mo/day/yr) 09/26/07

贸