RN	W~1	12	WATER	R WELL RECOR	D Form W	WC-5 KSA 82a	a-1212			
County: 1	10nta	TER WELL:	Fraction NE 1/4	SW 1/4	SE 1/4	Section Number 25		Number S 4 S	Range Number R 16 E/W	
Distance a		from nearest tow	vn or city street ad	dress of well if	located within	city?		•	, • -	
MATE	NELL OV	WED FAR	MLAND I	LLUGUST	6167	INC.				
WATER	Address Bo	x # : P.O.E	SAY EZA	,,,	D . CC .		Poord /	of Agricultura	Division of Water Resource	
717#, 31. / 7ib/ Stata	ZID Code	COF	EYVILLE	VS	67237			ition Number:	Division of water nesource	
LOCATI	, ZIP CODE	OCATION WITH	PEDTUCE		737	7.0				
AN "X"	IN SECTIO	N BOX:								
- w	 	ZE E	WELL'S STATIC Pump Est. Yield	WATER LEVEL test data: Wel gpm: Wel ter 8.3/.4i	I water was I water was n. to	ft. below land su ft. a ft. a ft. a ft., ft., water supply ld water supply	rface measured after after and 8 Air condition 9 Dewatering	I on mo/day/yr hours pu hours pu in ning 11	umping gpm umping gpm to ft. Injection well Other (Specify below)	
	i		Was a chemical/b	acteriological sa	mple submitted	I to Department? Y	es(160)); If yes	, mo/day/yr sample was sub	
_		\$	mitted				ater Well Disinfe			
TYPE (OF BLANK	CASING USED:		5 Wrought iron	8 (Concrete tile	CASING	JOINTS: Glue	d Clamped	
1 Ste	eel	3 RMP (S	R)	6 Asbestos-Cer	ment 9 (Other (specify below	w)	Weld	led	
(2) PV	′C	4 ABS	12	_7 Fiberglass				Thre	aded	
Blank casi	ng diameter	·		Oft., Dia		in. to	ft., Dia		in. to ft.	
Casing hei	ight above I	and surface	2.4	in., weight			ft. Wall thickne	ss or gauge N	₁₀ Schelue 40	
TYPE OF	SCREEN C	R PERFORATIO				? ℃vc		Asbestos-cem		
1 Ste	eel	3 Stainless	s steel	5 Fiberglass		8 RMP (SR)	11	Other (specify))	
2 Brass 4 Galvanized steel				6 Concrete tile		9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:				5	Gauzed wrapp	ed	8 Saw cut		11 None (open hole)	
	1 Continuous slot (3) Mill slot 6 Wire wrapp						9 Drilled holes			
	uvered shut	•	ev nunched							
		ED INTERVALS:	From	3,0	to 7	3.0 # Ero	m	ft :		
GROUT Grout Inter What is th 1 Se 2 Se	MATERIAI vals: Fro e nearest se ptic tank wer lines	purce of possible 4 Later 5 Cess	From cement ft. to	Dement grout 10 Live 7 Pit privy 8 Sewage lagoon 12 Fert		Other Other ft. to Other ft. to f		to ftft. toft sbandoned water well Dil well/Gas well		
	•	ver lines 6 Seep		9 Feedy	ard		cticide storage			
	rom well?	TH KE	PINERY	00	500		iny feet?	DITICONO	INTERVALO	
FROM	то		LITHOLOGIĆ L	_UG	FRO	ом то		PLUGGING I	INTERVALS	
^ O	10 n	DOMIN	CUTY C	/ 4.0/						
0.0	10.0	-Mais	SILTY C T/STIFF						PARTY STATE OF THE	
		2 7012	175117							
							The state of the s			
18,0	26.0	BROWN	SAND }	GRAVE	L					
			+							
26.0	26.0	GRAY :	SHALE							
		- DRY	HARD							
		- '//	· · · · · ·							
				,	_			andres and all alternate Makes in challen - Party - 178		
CONT	ACTOR'S		D'S CEDTIEICATIC	ON: This water	voll was /1) as	netructed (2) res	netructed or "	3) plugged un	der my jurisdiction and	
		7	30-94	JIN. THIS Water V	veii wasy (1) ca				der my jurisdiction and was	
-	on (mo/day	, you 	751	This Mrs	tor Moll Boss				nowledge and belief. Kansa D - 9 4	
		's License No.	to I Cana	_ 1	1 - 1	rd was completed		LA	~/	
		ime o#>>>c)		onmento	-	Hriesby (signa	The same of the sa	The same		
			pen. PLEASE PRESS FII Topeka, Kansas 66620				e the correct answ WNER and etain of	ne for your record	copies to Kansas Department s.	
J. 110011		,						,		