

1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SE 1/4 Section Number 25 Township Number T 34 S Range Number R 16 EA

Distance and direction from nearest town or city street address of well if located within city?  
1/8 mi north of North Linden

2 WATER WELL OWNER: Farmland Industries  
RR#, St. Address, Box #: North Linden Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: Coffeyville, KS 67337 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SE quadrant.]

4 DEPTH OF COMPLETED WELL: 27.9 ft. ELEVATION:  
Depth(s) Groundwater Encountered 1. 23 ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield gpm: Well water was ft. after hours pumping gpm  
Bore Hole Diameter: 7.25 in. to 27.9 ft., and in. to ft.  
WELL WATER TO BE USED AS:  
5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter: 2 in. to 17.9 ft., Dia in. to ft., Dia in. to ft.  
Casing height above land surface: 24 in., weight lbs./ft. Wall thickness or gauge No. 0.18 in.  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
SCREEN-PERFORATED INTERVALS: From 17.9 ft. to 27.9 ft., From ft. to ft.  
GRAVEL PACK INTERVALS: From 15.9 ft. to 27.9 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other concrete  
Grout Intervals: From 2 ft. to 13.9 ft., From 13.9 ft. to 15.9 ft., From 0 ft. to 2 ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Surface Pond  
Direction from well? How many feet? 30 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	clay - brown			
16	20	silt - sand - brown - very fine			
20	27.9	sand - brown - very fine			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-4-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 538. This Water Well Record was completed on (mo/day/yr) 3-27-91 under the business name of Fugro-McClelland by (signature) Charles Strout

OFFICE USE ONLY  
T  
R  
EM  
SEC.  
1/4  
1/4  
1/4