			Form WWC-5	Div	ision of Water R	esources; App. No.		
1 LOCA	ATION OF	WATER WELL:	Fraction		Section Number	er Township Nu	mber Range Number	
County: Montgomery SE ½ SW ½ SW ½ 35 T 34 S R 16 E Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)								
located within city? 703 Ellis St, Coffeyville, KS Latitude: N 37.03651°								
Longitude: W 95 635429								
2 WATER WELL OWNER: USD #445					Elevation: RIM: 743.89; TOC: 743.62 Datum: above mean sea level Data Collection Methods level			
RR#, St. Address, Box # : 615 Ellis St City, State, ZIP Code : Coffeyville, KS, 67337-3427					Data Collection Method: legal survey			
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 15 ft.								
LOCATON MW10								
1	I AN "X" I	N Depth(s) Groun	dwater Encountered 1			2	ft. 3 ft.	
SECT	ION BOX:	WELL'S STAT	TIC WATER LEVEL	Dry f	t. below land su	rface measured or	n mo/day/yr 6/30/09	
	N Pump test data: Well water was ft. after hours pumping gpm							
Est. Yield gpm: Well water was ft. after hours pumping gpm								
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
W Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10)Monitoring well								
SW SE Was a chamical/la statista and a submitted to Danatus at 2. Was a No. 16 years and 1.								
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X								
Sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded O PVC								
5 TYPE	OF CASI	NG USED: 5	Wrought Iron	8 Concre	te tile Cz	ASING JOINTS: (Glued Clamped	
1 Ste	eel	3 RMP (SR) 6	Asbestos-Cement	9 Other (specify below)	,	Welded	
Plank and	/C ina diamata	4 ABS /	r idergiass			A Dia	in to	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded (2) PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 3 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.27 ft., Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous elet. (D.Mill elet. 5. Gauge pyropped 7. Torch eut. 0. Drilled heles. 11. None (open hele)								
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 3 ft. to 15 ft. From ft. to ft. From 2.5 ft. to 15 ft. From ft. to ft.								
SCREEN	-PERFORA	TED INTERVALS:	From 3	ft. to	15 ft.	From	ft. to ft.	
		ė	From 2.5	ft. to	15 ft.	From	ft. to ft.	
GR	RAVEL PAG	CK INTERVALS:	rrom	π. το	It.	From	π. το π.	
			From	. ft. to	ft.	From	ft. to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1 ft Grout Intervals From 1 ft. to 2.5 ft. From ft. to ft. From ft. to ft.								
Grout Intervals From 1 ft. to 2.5 ft. From ft. to ft. From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify								
2 Sewer lines 5 Cess pool 8 Sewage lagoon (11) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? Northwest/west 12 Fertilizer storage 15 Oil well/ gas well How many feet? ~150 ft								
FROM	TO		LOGIC LOG				INTERVALS	
0	4		t, brown, stiff, moist	FROM	10	PLUGGING	INIERVALS	
4	8	Clay with trace sile		-				
		brown, stiff, moist						
8	15		nered, soft, brown to					
	 	light brown		 				
					Flus	hmount waiver f	rom BOW	
7 CONT	DACTOR	CODIANDONA	Dis CERTIFICATIO	N. This	votor vostl) honoteneted (2)	constructed or (2) -1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/30/09 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed on (mo/day) year) 7/23/09								
under the b	ousiness name	of Larsen & Asso	ciates, Inc.	by (signat	ure)			
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water.								
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.								