


MW 3

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SE 1/4 Section Number 36 Township Number T 34 S Range Number R 16 BW  
 County: MONTGOMERY

Distance and direction from nearest town or city street address of well if located within city?  
620 E 8TH STREET, COFFEYVILLE, KS

2 WATER WELL OWNER: EDDY'S ONE STOP  
 RR#, St. Address, Box #: 302 N OHIO Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: COFFEYVILLE, KS 67337 Application Number: —

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 20.5 ft. ELEVATION: —  
 Depth(s) Groundwater Encountered 1. ~15 ft. 2. — ft. 3. — ft.  
 WELL'S STATIC WATER LEVEL: 6.57 ft. below land surface measured on mo/day/yr 4/15/98  
 Pump test data: Well water was — ft. after — hours pumping — gpm  
 Est. Yield — gpm Well water was — ft. after — hours pumping — gpm  
 Bore Hole Diameter: 8.5 in. to 20.5 ft., and — in. to — ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-3  
 Was a chemical/bacteriological sample submitted to Department? Yes — No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes — No X

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped —  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded —  
 7 Fiberglass Threaded X  
 Blank casing diameter 2 in. to 10.5 ft. Dia — in. to — ft. Dia — in. to — ft.  
 Casing height above land surface 0 in., weight SCH 40 lbs./ft. Wall thickness or gauge No. —  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) —  
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) —  
 SCREEN-PERFORATED INTERVALS: From 10.5 ft. to 20.5 ft., From — ft. to — ft.  
 From — ft. to — ft., From — ft. to — ft.  
 SAND GRAVEL PACK INTERVALS: From 9 ft. to 20.5 ft., From — ft. to — ft.  
 From — ft. to — ft., From — ft. to — ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other —  
 Grout Intervals: 2 From 0 ft. to 7 ft., 3 From 7 ft. to 9 ft., From — ft. to — ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	SOIL			
1.5	8.5	CLAY (CL)			
8.5	14	SILT W/ SOME CLAY (ML)			
14	20	SAND W/ SOME SILT (SP)			
20	TD	END OF BOREHOLE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/22/98 4/13/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 3/18/98 under the business name of A&I by (signature) ADUNCAN Fr M Drake

OFFICE USE ONLY  
T  
R  
EW  
SEC.