1 LOCATION OF WATER WELL:	Fraction		Secti	on Number	Township	Number	Range Nu	nher
		SE 1/4 SE		18	т 34		R 17	STANSOTHERAS.
Distance and direction from nearest to								
Northeast of intersection of h								
2 WATER WELL OWNER: Amer		Wire Corp. c/o Le	eviton Ma	anufactı	uring Co., In	c.		
RR#, St. Address, Box # : 201 N					Board of Agr	riculture, Divi	sion of Water Re	esources
City, State, ZIP Code : <b>Melvi</b>	lle, NY 11747	e, NY 11747  Application Number:  4 DEPTH OF COMPLETED WELL  Depth(s) Groundwater Encountered 1 15 ft 2 ft 3						
LOCATE WELL'S LOCATON WIT	H 4 DEPTH OF C	ONADI ETED MELL	20	4 55	VATIONI	736	91 (TOC)	
AN A IN SECTION BOX.	Donth(s) Grounds	votor Engagnetared 1	15	<sup>  </sup>	VATION.		21 (100)	
	Deptin(s) Grounds	vater Ericodificied		1	l. &		J	, FL.
NW NE		WATER LEVEL						
<u></u>	F C-4 Viald	test data: Well water w	vas		n. aner 	nours p	umping	gpm
E- Caratra Control Con	- Est. Held	gpm: Well water v	vas 20		ii. ailei	nours p	umping	gpm
SW SE - <del></del>	WELL WATER TO	er <b>0.23</b> in. to DBE USED AS: 5 Pub	olic water su	nnlv	8 Air condit	ionina 11	. to L. Injection well	π.
SVV SE X	1 Domestic	er <b>8.25</b> in. to D BE USED AS: 5 Pub 3 Feed lot 6 Oil	field water s	upply	9 Dewaterin	ng 12	Other (Specify	/ below)
	2 Irrigation	4 Industrial 7 Lav	vn and garde	en (domesti	ic) 10 Monitori	ng well		
S		acteriological sample su						
	submitted				ater Well Disinfed			
TYPE OF BLANK CASING USED:		5 Wrought Iron	8 Concre				d Clam	
Manuel	P(SR)	6 Asbestos-Cement				Weld		
2 PVC 4 ABS	` '	7 Fiberaless	,		paket reasonable	Thread	CONTRACTOR OF THE PROPERTY OF THE PARTY OF T	sh
Blank casing diameter 2		· ·					ENTER DE VINE AUTORIO DE CONTROL	SERVENDO DE LA COMPANION DE LA
Casing height above land surface	32	n., weight $0$ .	703	lbe /ft	Wall thickness of	or gauge No	SCH.	
YPE OF SCREEN OR PERFORATION		n., weight	7	108./IL. 2\/C	10 As	heetoe-ceme	nt	
		5 Fiberglass						
2 Brass 4 Galv	anized steel	6 Concrete tile	9 /	ABS		ne used (ope		
CREEN OR PERFORATION OPEN		5 Gauzeo			8 Saw cut		11 None (oper	n hole)
1 Continuous slot	B Mill slot	6 Wire wr	rapped		9 Drilled hole			
2 Louvered shutter 4	Key punched	7 Torch o	ut		10 Other (spe	ecify)		
SCREEN-PERFORATED INTERVAL	S: From	<b>24</b> ft. to	29	ft.	From	ft. te	0	ft.
		ft. to						
GRAVEL PACK INTERVALS		<b>21</b> ft. to	29	ft.	From	ft. t	0	ft.
	From	ft. to		ft.	From	ft. t	0	ft.
GROUT MATERIAL: 1 Nea	t cement 2	Cement grout	3 Bent	onite	4 Other			
Grout Intervals From 2	ft. to 21	ft. From	ft. to	<del>)</del>	ft. From		ft. to	ft.
What is the nearest source of possible					stock pens			
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel		15 Oil	well/ Gas well	
2 Sewer lines	5 Cess pool	8 Sewage la	agoon	12 Ferti	lizer storage			w)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard			cticide storage			•
Direction from well?				How many	y feet?			
FROM TO CODE		OGIC LOG	FROM	TO	Р	LUGGING IN	ITERVALS	
0 10 S	ilty Clay, gray					, , , , , , , , , , , , , , , , , , , ,		
	andy Clay, yell							
	and, well graded rained	l, very fine to coarse						
	ravel, medium t	o coarse grained		<del> </del>				
	ravel, mealant	o course granica		<del> </del>				
				<del> </del>				
	- INDA-A-ROBERT - INDA-A-ROBER			GPS Coord				
				<b>_</b>	Northing: 1			
	IDD10 0	A.L			Easting: 21			-
7 CONTRACTOR'S OR LANDOWN			P. Salami Myzgorky and Con-					
	06/27				true to the best o			(ansas
Water Well Contractor's License No.		531	This W	ater Well R	lecord was/comp	leted on (mo/	day/yr) <b>07/</b>	01/11
under the business name of	Geotechnic	al Services Inc.		(signature)		1 ly		
INSTRUCTIONS:. Please fill in bla Jackson St., Ste. 420, Topeka, Kar	inks and circle the corresponding the corresponding to the corresponding	ect answers. Send three co	opies to Kansa	as Departme	ent of Health and E	nvironment, Bu	reau of Water, 10	100 S W