

1 LOCATION OF WATER WELL: County: Montgomery	Fraction SW ¼ NW ¼ NW ¼	Section Number 31	Township Number T 34 S	Range Number R 17 E/W
--	-----------------------------------	-----------------------------	----------------------------------	--

Distance and direction from nearest town or city street address of well if located within city?

400 N. Linden, Coffeyville

2 WATER WELL OWNER: Coffeyville Resources Refining & Marketing, LLC RR#, St. Address, Box # : 400 N. Linden City, State, ZIP Code : Coffeyville, KS, 67337	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 32 ft. ELEVATION: 718.96
--	--

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was **NA** ft. after hours pumping gpm

Est. Yield **NA** gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter **12.25** in. to **22** ft., and **6** in. to **32** ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only **10** Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 6 in. to 22 ft., Dia 2 in. to 27 ft., Dia in. to ft.			Threaded. <input checked="" type="checkbox"/>
Casing height above land surface -35.04 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 27 ft. to 32 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 25 ft. to 32 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Concrete
Grout Intervals: From 0 ft. to 0.5 ft., From 0.5 ft. to 22 ft., From 22 ft. to 25 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Clay, tr. silt,			
5	7.5	Clay, w/sand and some silt,			
7.5	10	No Recovery,			
10	10.5	Clay, w/sand and some silt,			
10.5	11.5	Sand, w/clay,			
11.5	15	Clay, w/sand and some silt,			
15	17.5	No Recovery,			
17.5	22	Gravel, limestone,			
22	22.5	Limestone, intensely fractured,			
22.5	25	Limestone, sl. fractured,			
25	32	Shale, unfractured,			
					RMW-306, Abovegrade

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/23/2011 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 9/10/11
under the business name of GeoCore, Inc. by (signature) <i>Debra Bell</i>