WATER WELL RECORD Form WWC-5 Division of Water Resource	es, App. 140.					
1 LOCATION OF WATER WELL: Fraction Section Number T	T 34 S R 17 E					
County: Montgomery NW 2 SW 2	3003					
2 WATER WELL OWNER: KDHE RR#, St. Address, Box # : 1000 SW Jackson blvd City, State, ZIP Code : Topeka KS Elevation: RIM: 7 Datum: WGS84 Data Collection Met	15.86; TOC: 715.25					
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 15.0	ft.					
I OCATION MW2						
WITH AN "X" IN Depth(s) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL 10.75 ft. below land surface	measured on mo/day/yr 8/0/14					
Pump test data: Well water was ft. after hours pumping gpm						
Est Yield gpm: Well water was ft. after nours pumping gpm						
1 1 1 WELL WATER TO BE USED AS: 5 Public water slipply 8 Air conditioning 11 injection with						
WELD WATER TO BE OBJECT TO STAND A PROPERTY OF THE PROPERTY OF	ering 12 Other (Specify below) bring well					
SW SE Was a chemical/hacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs						
Sample was submitted water were	1 Disinfected? Yes No X					
5 Wrought Iron 8 Concrete tile CASIN	G JOINTS: Glued Clamped					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)	Welded					
PVC 4 ABS 7 Fiberglass	Threaded X					
Blank casing diameter 2 in. to 5 ft., Dia in. to ft., D	Dia in. to tt.					
Casing height below land surface 0.61 ft., Weight lbs./ft. Wall t	thickness or gauge No.					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 5 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.61 ft., Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 5 ft. to 15 ft. From ft. to ft.						
SCREEN PERFORATED INTERVALS: From 5 ft. to 15 ft. From	n ft. to ft.					
From ft. to ft. From	n ft. to ft.					
GRAVEL PACK INTERVALS: From 3 ft. to 15.65 ft. From	n ft. to ft.					
SCREEN-PERFORATED INTERVALS: From 5 II. to 15 III. From 5 From 5 II. to 15 III. From 6	m ft. to ft.					
The composition was recorded to the first terms of the composition of	# D D D C T C T					
Grout Intervals From 1 ft. to 3 ft. From ft. to ft.						
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 10 Livestock pens 11 Insecticide Storage 14 Abandoned water well 12 Fertilizer storage 15 Oil well/ gas well						
Discould from which is a second of the secon	PLUGGING INTERVALS					
FROM TO LITHOLOGIC LOG FROM TO 0 0.5 Concrete						
0.5 5 Black silty clay						
5 15.65 Gray silty clay						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/4/14 and this record is true to the best of my knowledge and belief Kansas Water Well Contractor's License No. 757 This Water Well Record was completed on (mo/day/year) 9/3/14						
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.						

TRITERRA LAND SERVICES

KGS Capy

P.O. Box 546 Clearwater, Kansas 67026 Cell (316) 648-3617 Fax (620) 584-4371 E-mail: triterrals@yahoo.com

SURVEYING OF MONITORING WELLS 701 NORTHEAST STREET COFFEYVILLE, KANSAS

The above site is in Section 31, Township 34 South, Range 17 East of the Sixth Principal Meridian, Montgomery County, Kansas. The Southeast corner of Section 31 was assigned coordinates of 00.00 North and 00.00 West.

The control point from the Jump Start #8 site to the north was used for vertical control. This site's control point was established as a chiseled 'X' on the southeast corner of the old sign base at the north edge of the site.

The Latitude and Longitude were recorded from a GPS device. The site is located on the quad map titled "Coffeyville East".

ID SE CORNER 31-34S-17E	NORTH 00.00	WEST 00.00	LATITUDE	LONGITUDE	ELEVATION
J1-345-17E		(Irregular Section)			
Control Point	894.41	6302.29	37.03682	95.59920	715.94
MW-1 SW NW SW SW	783.46	6349.65	37.03651	95.59936	RIM 715.79 TOC 715.40
MW-2 SW NW SW SW	821.91	6328.66	37.03663	95.59928	RIM 715.86 TOC 715.25
MW-3 SW NW SW SW	777.69	6279.14	37.03651	95.59913	RIM 715.33 TOC 715.03
MW-4 SW NW SW SW	866.67	6336.25	37.03675	95.59932	RIM 716.02 TOC 715.52
MW-5 SW NW SW SW	844.77	6497.14	37.03670	95.59986	RIM 715.25 TOC 714.72
MW-6 SW NW SW SW	753.62	6401.39	37.03645	95.59953	RIM 716.18 TOC 715.63
MW-7 SW NW SW SW	700.08	6333.16	37.03632	95.59937	RIM 715.53 TOC 714.92
MW-8 SW NW SW SW	725.23	6281.97	37.03636	95.59913	RIM 714.83 TOC 714.27

