Carry Continuous slot Clark Cl	WATER WELL RECORD	D Form WWC-	5 Division of Water	r Resources; App. No.				
Control within city? // Northeast St., Colleyvine, k.S. Control within city? // Northeast St., College within city? // Northeast within city? // Northeast St., College within city? // Northeast within city? // Northe	T TOCHTON OF WATER W	WELL. Emotion	Section Num	nber Township Number T 34 S	Range Number R 17 E			
PATTER WELL OWNER: KDHE RR#, St. Address, Box # 1000 SW Jackson blvd City, State, ZIP Code Topeka KS LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL Pump test data: Well water was ft. after hours pumping gpm USLL WATER TO BE USED AS: 5 Public water supply UWL WATER TO BE USED AS: 5 Public water supply UWL WATER TO BE USED AS: 5 Public water supply UW Sa a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted UW as a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted UW as a chemical/bacteriological sample submitted to Department? Yes No X STYPE OF CASING USED: 5 Wrought Iron Steel 3 RMP (SR) 6 Asbestos-Cement UW as a chemical/bacteriological sample submitted to Department? Yes No X STYPE OF CASING USED: 5 Wrought Iron Steel 3 RMP (SR) 6 Asbestos-Cement UW as a chemical/bacteriological sample submitted to Department? Yes No X STYPE OF CREEN OR SEED: 5 Wrought Iron Steel 3 RMP (SR) 6 Asbestos-Cement UW as a chemical/bacteriological sample submitted to Department? Yes No X STYPE OF CREEN OR SEED: 5 Wrought Iron Steel 3 RMP (SR) 6 Asbestos-Cement UW as a chemical/bacteriological sample submitted to Department? Yes No X STYPE OF CREEN OR PERFORATION MATERIAL Steel 3 Stailless seed: 5 Fiberglass Threaded X STOPPE OF SCREEN OR PERFORATION MATERIAL STYPE OF SCREEN OR PERFORATION OPENINGS ARE:	Boonted within city/ /III Northeagt St. Cottevville, K.S Lauluuc, IN 37,03073							
RR#f, St. Address, Box # 1000 SW Jackson blvd City, State, ZIP Code : Topeka KS 1 LOCATO WITH AN "X" IN SECTION BOX: N WELL'S STATIC WATER LEVEL. 11.13 ft. below land surface measured on mo/day/yr 8/6/14. Pump test data: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic (lawn & garden) WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 2 Impaired in the conditioning 11 Injection well 2 Impaired in the conditioning 11 Injection well 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X, 1f yes, mo/day/yrs Sample was submitted TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Was a chemical/bacteriological sample submitted to Department? Yes No X. STYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in to 4.95 ft, Dia in to ft, Dia in to ft. Casing height below land surface 0.55 ft, Weight 1 lbs/ft. Wall bickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 5 CREEN-PERFORATION OPENINGS ARE: 1 Continuous slot 3 Similess steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) SCREEN-PERFORATED INTERVALS: From 4,95 ft, to 14.95 ft, From ft. to ft. From ft. t	2 WATER WELL OWNED.	VDUE	Longitude:	W 95.59953° RIM: 716.18: TOC: 715.0	63			
City, State, ZIP Code : Topeka KS 8 LOCATE WELL'S 8 LOCATON WITH AN "X" IN SECTION BOX: N WELL'S STATIC WATER LEVEL 11.13 ft. below land surface measured on mo/day/yr 8/6/14 Pump test data: Well water was ft. after hours pumping gpm Est, Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) I Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) I Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) I Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X, If yes, mo/day/yrs Sample was submitted 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped I Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in to 4,95 ft., Dia in to ft. Casing height below land surface 0.55 ft., Weight TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stairless steel 5 Fiberglass 7) PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 1 Continuous slot Mall slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 Rt. to 14.95 ft. From ft. to ft	RR#, St. Address, Box #	1000 SW Jackson blvd	Datum:	WGS84	_			
WITH AN "X" IN SECTION BOX: N	City State, ZIP Code :	Topeka KS	Data Collect	tion Method: legal survey	7			
WITH AN "X" IN SECTION BOX: N	3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 14.95 ft.							
Pump test data: Well water was ft. after hours pumping gpm well water supply 8 Air conditioning 11 injection well 10 ments of ft. Ship well water supply 9 Dewatering 12 Other (Specify below) 10 Monitoring well 10 Monitoring well 20 Charles was attemed a submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted to Department? Yes No X; If yes, mo/day/yrs water well Disinfected? Yes No X; If yes, mo/day/yrs water well Disinfected? Yes No X; If yes, mo/day/yrs water well Disinfected? Yes No X; If yes, mo/day/yrs water well Disinfected? Yes No X; If yes, mo/day/yrs water supply 9 Dewatering 1 Dinection well 1 Domestic (lawn & garden) (Domestic (lawn & garden) (Domestic department? Yes No X; If yes, mo/day/yrs water supply 9 Dewatering 1 Domestic (lawn & garden) (Domestic department? Yes No X; If yes, mo/day/yrs water supply 9 Dewatering 1 Domestic (lawn & garden) (Domestic department? Yes No X; If yes, mo/day/yrs water supply 9 Dewatering 1 Domestic (lawn & garden) (Domestic department? Yes No X; If yes, mo/day/yrs water supply 9 Dewatering 1 Domest	LOCATON WITH AN "Y" IN Denth	(s) Groundwater Encountered 1	141 44 0	ft. 2 ft. 3	ft.			
Pump test data: Well water was fi. after hours pumping gpm well after hour	SECTION BOX: WELL	'S STATIC WATER LEVEL	11.13 ft. below land	surface measured on mo/	day/yr 8/6/14			
WELL WATER TO BE USED AS: 5 Public Water supply 9 Dewatering 12 Other (Specify below) 1 Domestic 3 Feed to 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 0 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Welded Threaded X 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X Blank casing diameter 2 in to 4.95 ft., Dia in to ft., Dia in to ft. Casing height below land surface 0.55 ft., Weight Ibss/ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Continuous slot 5 Mill slot 5 Gauze wrapped 2 Continuous slot 5 Mill slot 5 Gauze wrapped 2 Continuous slot 5 Mill slot 5 Gauze wrapped 5 From 4.95 ft. to 14.95 ft. From ft. to ft. Fr	N	Pump test data: Well water	r was ft. af	fter hours pump	ping gpm			
WELL WATER TO BE USED AS: 5 Public Water supply 9 Dewatering 12 Other (Specify below) 1 Domestic 3 Feed to 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 0 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Welded Threaded X 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X Blank casing diameter 2 in to 4.95 ft., Dia in to ft., Dia in to ft. Casing height below land surface 0.55 ft., Weight Ibss/ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Continuous slot 5 Mill slot 5 Gauze wrapped 2 Continuous slot 5 Mill slot 5 Gauze wrapped 2 Continuous slot 5 Mill slot 5 Gauze wrapped 5 From 4.95 ft. to 14.95 ft. From ft. to ft. Fr	Est. Yi	ield gpm: Well water	r was ft. af	fter hours pump	oing gpm			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in to 4.95 ft., Dia in to ft., Dia in to ft. Casing height below land surface 0.55 ft., Weight Ibs/ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 5 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) 5 SCREEN-PERFORATED INTERVALS: From 4.95 ft. to 14.95 ft. From ft. to ft. From ft. to 15.55 ft. From ft. to ft. From ft. to 15.55 ft. From ft. to ft. From ft. to 15.55 ft. From ft. to ft. From ft. to 15.55 ft. From ft. to ft. From	NW - NE - WELL	- WATER TO BE USED AS:	S Public Water supply	8 All conditioning 11	injection wen			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted to Department? Yes No X; If yes, mo/day/yrs Water Well Disinfected? Yes No X; If yes, mo/day/yrs was was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs No X; If yes, mo/day/yes, mo/day/yes, mo/day/yes, mo/day/yes, mo/day/yes, mo/day/yes, mo/day/yes, mo/day/yes, mo/day/yes	W E I Don	ation 4 Industrial 7 Domest	ic (lawn & garden) (10)Monitoring well				
Sample was submitted Steel								
Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X	Was a Sampl	chemical/bacteriological samp e was submitted	le submitted to Departm Wa	nent? Yes No X ater Well Disinfected? Yes	; If yes, mo/day/yrs s s No X			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X Blank casing diameter 2 in to 4.95 ft., Dia in to ft., Dia in to ft. Casing height below land surface 0.55 ft., Weight Ibs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 5 CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) 5 SCREEN-PERFORATED INTERVALS: From 4.95 ft. to 14.95 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 3 ft. to 15.55 ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1' Grout Intervals From 1 ft. to 3 ft. From ft. to ft. Fr	5 TYPE OF CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glue	d Clamped			
Blank casing diameter 2 in to 4.95 ft., Dia in to ft., Dia in to ft. Dia in to ft. Casing height below land surface 0.55 ft., Weight Ibs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 5 From 4.95 ft. to 14.95 ft. From ft. to ft. From ft	1 Steel 3 RMP (SI	R) 6 Asbestos-Cement	9 Other (specify belo	(w) Weld	led			
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 4.95 ft. to 14.95 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 3 ft. to 15.55 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1' Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well Direction from well? NE FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					aded X			
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 4.95 ft. to 14.95 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 3 ft. to 15.55 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1' Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well Direction from well? NE FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	Blank casing diameter 2	in. to 4.95 ft., Dia	in. to	tt., Dia 11	1, to II.			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot	Casing height below land surface	0.55 It., Weight	108./11	. Wan unexhess of gauge	, 110.			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot	1 Steel 3 Stainless steel	5 Fiberglass (7) PVC	9 ABS	11 Other (specify))			
1 Continuous slot 2 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 4.95 ft. to 14.95 ft. From ft. to ft. From ft. From ft. To ft. F	2 Brass 4 Galvanized stee	el 6 Concrete tile 8 RM (S	R) 10 Asbestos-Cen	nent 12 None used (op	en hole)			
SCREEN-PERFORATED INTERVALS: From 4.95 ft. to 14.95 ft. From ft. to ft. To ft. From ft. To ft. From ft. To ft. To ft. To ft. From ft. To ft.	1 Continuous slot (3) Mi	OPENINGS ARE: 11 slot	d 7 Torch cut 9	Drilled holes 11 Nor	ie (open hole)			
GRAVEL PACK INTERVALS: From 3 ft. to 15.55 ft. From ft. to ft.	2 Louvered shutter 4 Ke	y punched 6 Wire wrapped	8 Saw Cut 10	Other (specify)				
GRAVEL PACK INTERVALS: From 3 ft. to 15.55 ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout Grout Intervals From 1 ft. to 3 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well Direction from well? NE How many feet? ~80' FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 0.3 Asphalt	SCREEN-PERFORATED INTE	RVALS: From 4.95	ft. to 14.95	ft. From 11.	to ft			
Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. From ft. From ft. To ft. From ft. Fr	CDAVEL DACK INTER	VAIS: From 3	ft. to 15.55	ft. From ft.	to ft.			
Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. From ft. From ft. To ft. From ft. Fr	ORAVELTACK INTER	From	ft. to	ft. From ft.	toft.			
Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. T	CDOUT MATERIAL 1	Neat cement 2 Cement group	t (3 Rentonite (4)	Other Concrete: 0-1'				
What is the nearest source of possible contamination: 1 Septic tank 2 Lateral lines 7 Pit privy 2 Sewer lines 3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 12 Fertilizer storage 15 Oil well/ gas well How many feet? ~80' FROM TO PLUGGING INTERVALS	Grout Intervals From 1	ft. to 3 ft. From	ft. to	ft. From	ft. to ft.			
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well Direction from well? NE How many feet? ~80' FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Asphalt	What is the nearest source of possible contamination:							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? NE FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Asphalt								
Direction from well? NE How many feet? ~80' FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 0.3 Asphalt	2 Sewel lilles 3 Cess pool 8 Sewage lagoon (1) I do sterings							
0 0.3 Asphalt	Direction from well? NE How many feet? ~80'							
	FROM TO	LITHOLOGIC LOG	FROM TO	PLUGGING IN	TERVALS			
0.3 15.55 Brown sury clay		4						
	0.3 15.55 Brown SII	ty clay						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged								
and this record is true to the best of my knowledge and belief.								
Kansas water well Collifactor's Electise No								
Sond ton three gonies to Kaness Department of Heart and Environment Bureau of Water.								
O Lind V D A Still and Environment Diversity of Water	INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Heath and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one is WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.							

TRITERRA LAND SERVICES

KGS Capy

P.O. Box 546 Clearwater, Kansas 67026 Cell (316) 648-3617 Fax (620) 584-4371 E-mail: triterrals@yahoo.com

SURVEYING OF MONITORING WELLS 701 NORTHEAST STREET COFFEYVILLE, KANSAS

The above site is in Section 31, Township 34 South, Range 17 East of the Sixth Principal Meridian, Montgomery County, Kansas. The Southeast corner of Section 31 was assigned coordinates of 00.00 North and 00.00 West.

The control point from the Jump Start #8 site to the north was used for vertical control. This site's control point was established as a chiseled 'X' on the southeast corner of the old sign base at the north edge of the site.

The Latitude and Longitude were recorded from a GPS device. The site is located on the quad map titled "Coffeyville East".

ID SE CORNER 31-34S-17E	NORTH 00.00	WEST 00.00	LATITUDE	LONGITUDE	ELEVATION
J1-345-17E		(Irregular Section)			
Control Point	894.41	6302.29	37.03682	95.59920	715.94
MW-1 SW NW SW SW	783.46	6349.65	37.03651	95.59936	RIM 715.79 TOC 715.40
MW-2 SW NW SW SW	821.91	6328.66	37.03663	95.59928	RIM 715.86 TOC 715.25
MW-3 SW NW SW SW	777.69	6279.14	37.03651	95.59913	RIM 715.33 TOC 715.03
MW-4 SW NW SW SW	866.67	6336.25	37.03675	95.59932	RIM 716.02 TOC 715.52
MW-5 SW NW SW SW	844.77	6497.14	37.03670	95.59986	RIM 715.25 TOC 714.72
MW-6 SW NW SW SW	753.62	6401.39	37.03645	95.59953	RIM 716.18 TOC 715.63
MW-7 SW NW SW SW	700.08	6333.16	37.03632	95.59937	RIM 715.53 TOC 714.92
MW-8 SW NW SW SW	725.23	6281.97	37.03636	95.59913	RIM 714.83 TOC 714.27

