

1 LOCATION OF WATER WELL: County: LABETTE	Fraction: SE 1/4 NE 1/4 SE 1/4	Section Number: 34 35	Township Number: T 34 S	Range Number: R 21 E
---	---------------------------------------	------------------------------	--------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

NORTH 3 RD. 1/2 BLOCKS NORTH OF CITY LIMITS

2 WATER WELL OWNER: ROBERT WITHROW RR#, St. Address, Box #: RR1 BOX 120 City, State, ZIP Code: CHETOPA KANSAS	Board of Agriculture, Division of Water Resources Application Number: NONE
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: 7 ft.
--	--

1 Mile

Depth(s) Groundwater Encountered: **1** ft. **7** ft. **3** ft.

WELL'S STATIC WATER LEVEL: **7** ft. below land surface measured on mo/day/yr **10/22/89**

Pump test data: Well water was **25** gpm. Well water was **10** ft. after **70** hours pumping **10/22/89** gpm

Est. Yield: **25** gpm. Well water was **10** ft. after **70** hours pumping **10/22/89** gpm

Bore Hole Diameter: **10** in. to **70** ft., and **10** in. to **70** ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes **X** No **X**; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **X** No **X**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded X
Blank casing diameter: 6 in. to 70 ft., Dia 18 in. weight 50 lbs./ft.			Threaded X
Casing height above land surface: 18 in.			lbs./ft. Wall thickness or gauge No. SDR 26
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 50 ft. to 70 ft.			
GRAVEL PACK INTERVALS:			
From 70 ft. to 30 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 30 ft. to 25 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	SILT			
6	20	CLAY			
20	30	LIME STONE			
30	45	CLAY			
45	55	COAL			
55	70	BLACK SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/22/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 501 This Water Well Record was completed on (mo/day/yr) 10/21/89 under the business name of CARRIER WATER WELL SERVICE by (signature) James H. Callier
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.

5010000068-50