

1 LOCATION OF WATER WELL: County: <u>Cherokee</u>	Fraction <u>SE 1/4 SW 1/4 NW 1/4</u>	Section Number <u>4</u>	Township Number <u>T 34 S</u>	Range Number <u>R 25E EW</u>
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3 MILES NORTH OF RIVERTON, KS - EAST OF ALT. 69 HWY - JAYHAWK PLANT WELL # CW-1

2 WATER WELL OWNER: <u>Chevron Chemical Company</u> RR#, St. Address, Box # : <u>6001 Bollinger Canyon Rd</u> City, State, ZIP Code : <u>Box 5047 San Ramon CA 94583</u>	Board of Agriculture, Division of Water Resource Application Number:
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>485</u> ft. ELEVATION: <u>841.53</u>
--	--

	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>87.08</u> ft. below land surface measured on mo/day/yr <u>7/18/95</u>
	Pump test data: Well water was <u>181.22</u> ft. after <u>20</u> hours pumping <u>80</u> gpm
	Est. Yield <u>300</u> gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter <u>17.5</u> in. to <u>28</u> ft., and <u>12 1/4</u> in. to <u>315</u> ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well <u>8" to 485'</u>
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> <u>X</u>	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
<u>1 Steel</u> 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u>	
2 PVC 4 ABS 7 Fiberglass Threaded	

Blank casing diameter 14 in. to 28 ft., Dia 8 in. to 315 ft., Dia in. to ft.

Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS <u>12 None used (open hole)</u>	

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut <u>11 None (open hole)</u>
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	

SCREEN-PERFORATED INTERVALS:	From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS:	From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement <u>2 Cement grout</u> 3 Bentonite 4 Other
Grout Intervals: From <u>0</u> ft. to <u>315</u> ft., From ft. to ft., From ft. to ft.	

What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage <u>16 Other (specify below)</u>	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage <u>Jayhawk Plant</u>	

Direction from well? East How many feet? 2600

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>10</u>	<u>Clay</u>			
<u>10</u>	<u>28</u>	<u>Limestone</u>			
<u>28</u>	<u>314</u>	<u>Cherty Dolomite</u>			
<u>314</u>	<u>316</u>	<u>Shale</u>			
<u>316</u>	<u>475</u>	<u>Cherty Dolomite</u>			
<u>475</u>	<u>485</u>	<u>Limestone</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/16/95</u> and this record is true to the best of my knowledge and belief. Kansa Water Well Contractor's License No. <u>102</u> This Water Well Record was completed on (mo/day/yr) <u>11-16-95</u> under the business name of <u>Kayne-Western</u> by (signature) <u>[Signature]</u>
--