

mw-6

1 LOCATION OF WATER WELL: County: <u>Cherokee</u>	Fraction <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>17</u>	Township Number T <u>34</u> S	Range Number R <u>25</u> <u>EW</u>
--	---	-----------------------------	----------------------------------	---------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

NE Corner of Jct 66 & 26/69 Alt., Riverton, Ks

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code	<u>Riverton Quik Stop Attn: Misty Sturgeon</u> <u>P.O. Box 514, Carthage, MO 64836</u>	Board of Agriculture, Division of Water Resource Application Number:
---	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>22</u> ft. ELEVATION: <u>17</u> ft.
--	---

Depth(s) Groundwater Encountered 1. 17 ft. 2. 12.65 ft. 3. 12/6/95 ft.

WELL'S STATIC WATER LEVEL 12.65 ft. below land surface measured on mo/day/yr 12/6/95

Pump test data: Well water was 8.625 in. to 22 ft. after 10 hours pumping gpm

Est. Yield gpm: Well water was 8.625 in. to 22 ft. after 10 hours pumping gpm

Bore Hole Diameter 8.625 in. to 22 ft. and 10 in. to 22 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well <u>mw-6</u>

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes 10 No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes 10 No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>10</u> Clamped <u>10</u>
------------------------------	----------------	-----------------	--

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 10

2 PVC 4 ABS 7 Fiberglass Threaded X

Blank casing diameter 2 in. to 12 ft. Dia 12 in. to 12 ft. Dia 12 in. to 12 ft.

Casing height above land surface 0 in. weight SCH 40 PVC lbs./ft. Wall thickness or gauge No. 10

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 12 ft. to 22 ft. From 12 ft. to 22 ft. From 12 ft. to 22 ft.

SAND GRAVEL PACK INTERVALS: From 11 ft. to 22 ft. From 11 ft. to 22 ft. From 11 ft. to 22 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 20 ft. to 9 ft. From 9 ft. to 11 ft. From 11 ft. to 11 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>Contaminated Si</u>

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	1.00	Asphalt			
1.00	20.00	Silty Clay (CL)			
20.00	21.00	Shale			
21.00	22.00	Limestone			
22.00	TD	End of Borehole			

Flush Mount
waiver
D. Taylor
9/5/95

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/29/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>585</u> . This Water Well Record was completed on (mo/day/yr) <u>12/10/95</u> under the business name of <u>Associated Environmental, Inc.</u> by (signature) <u>D. Taylor</u>
