WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	well: Cherokee Fraction SW 1/4 SW 1/4			Section number		Township number	Range number		
2. Distance and dire	ection from nearest town or city:	1/4 300 1/4			MINISTER STATE OF THE STATE OF	y of Galena, Ks	R	EDV	
R.R. or s					street:				
CITY, 510					ofe, zip code: Galena Ks 6. Bore hole dia. 10 in. Completion date				
4. Locate with "X" in section below: N						Well depth 260 ft. Completion date			
						7 Cable tool 🔀 Rotary Driven Dug			
NW NE						Hollow rod Jetted Bored Reverse rotary 8. Use: Domestic X Public supply Industry			
E GIST GIQX						Irrigation Air conditioning Stock			
E GHST GOX X WOLL						Lawn Oil field water Other 9. Casing: Material Street Height Above or below Threaded Welded Surface in.			
S 1-4						RMPPVCWeight 40.48 lbs./ft. Dia.10 in. to 502 ft. depth!Wall Thickness: inches or			
5. Type and color of material					То	Diain. toft. depth gage No. 4365			
D. I.C.				25		10. Screen: Manufacturer's n	ame	A CONTROL OF THE PARTY OF THE P	
Red Clay - Limestone Chert				0_	15	TypeDit.			
Gray Limestone Chert				15'	235	Slot/gauze Lengthft. andft.			
Gray Limestone Chert-trace gray shale				Z35	276'	ft. andft. Gravel pack?Size range of material			
Gray Limestone Chert				2701	385,	CONTROL OF THE CONTRO			
Gray Brown Limestone				385 ¹	430	12. Pumping level below land surfaces: 790 ft. after 2 hrs. pumping 401 g.p.m.			
Brown Gray Limestone trace chert				4-36	G40'				
Gray Brown Limestone trace chert				10-FS	725	13. Water sample submitted: mo./day/yr.			
Gray Brown Linestone chert				725	Soo'	Yes No Date C3Co19			
				300	890'	PTTless adapter Inches above grade			
Company of the second of the s				_ 9	1105	15. Well grouted? Yes With: Neat cement Bentonite Concrete			
Gray Dolomite Chert					l l	Depth: From ft. to 502 ft.			
Gray Dolomite				105	IIIO.	16. Nearest source of possible contamination: ft Type			
Gray Limestone Dodomite				110,	1580,	Well disinfected upon comple	·	No.	
Total Depth				260		17. Pump: Manufacturer's name	× Not installed	77	
				PERSONAL EIGHT SEATHARAIN		Model number		olts	
APPERATURE AND THE SECULOUS CONTRACTOR OF CONTRACTOR SECULOUS CONTRACTOR SECULOUS CONTRACTOR SECULOUS SECULOUS CONTRACTOR SECU		на поворя на почени поворя на почени в	STEELSHOOT PROVINCES STEELS ASSESSED AS MAN	erentekski kontakarene.		Length of drop pipe Type:	«» на сарасту ««»	y.p.m. <	
						Submersible Jet	Turbin	ocating	
The state of the s	(Use a second s	heet if needed)		TO THE WATER WATER		Centrifugal	Other	Sec	
18. Elevation:	19. Remarks: #3					20. Water well contractor's o This well was drilled under m		s report	
						is true to the best of my knowledge and belief.			
Hill Applic, No. 32041					Business rame L			cense No.	
Slope // / Upland					Audi ess Committee OCOST			OCO874 \$ 1	
valley		non ventorial vento esta constitución de la constit	Marcon Montellour Co. Anna Marcon Processor	TOPANIAN TOWNS AND		Signed Authorized representative Date			
Forward the white, blu	ue and pink copies to the Department	of Health and Environment				4	Form W\	WC-5	