	WATER	WELL RECORD	Form WWC-5			
LOCATION OF WATER WELL:	Fraction			tion Numbe		Range Number
County: Cow/sy	NW 1/4	NW 1/4 K/	W 1/4	3/	T 34 s	R 4 6W
Distance and direction from nearest to	AA '.		4	11	11 CHty Kight	4
XE COUNT OF			Mansas C	Ityji	KS of Way	MW#9
WATER WELL OWNER: 1014		1		, ,	'	
	W 18H	6			Board of Agricultur	e, Division of Water Resources
City, State, ZIP Code	DINVILCO	80201	740		Application Number	
LOCATE WELL'S LOCATION WITH	14 DEPTH OF CO	MPLETED WELL	38,0	. ft. ELEV	'ATION:	
AN "X" IN SECTION BOX:						t. 3
	WELL'S STATIC V	VATER LEVEL	ft. b	elow land s	urface measured on mo/day	/yr
NW NE	•					pumping gpm
						pumping gpm
<u>•</u> ,,,	Bore Hole Diamete	er. <i>.//.</i> /in. to	. کیگ ر		, and	.in. to \hdots
* W E	WELL WATER TO	BE USED AS:	5 Public wate	r supply	8 Air conditioning	11 Injection well
-	1 Domestic	3 Feedlot	6 Oil field wat			12 Other (Specify below)
3W 3C	2 Irrigation	4 Industrial	7 Lawn and g	arden only	Monitoring well	
	Was a chemical/ba	cteriological sample	submitted to De	epartment?	Yes; If y	yes, mo/day/yr sample was sub
· \$	mitted			W	/ater Well Disinfected? Yes	No
TYPE OF BLANK CASING USED:	!	5 Wrought iron	8 Concre	ete tile	CASING JOINTS: G	lued Clamped
1 Steel 3 RMP (S	SR)	6 Asbestos-Cement	9 Other	(specify belo	ow) W	elded
OPVC 4 ABS	. 17	7 Fiberglass				nreaded.x
Blank casing diameter 2. !!	in. to جباع	ft., Dia				in. to ft.
Casing height above land surface	 ir	n., weight <i>ふん</i> ょ	2.40	Ibs	s./ft. Wall thickness or gauge	∍ No
TYPE OF SCREEN OR PERFORATION	ON MATERIAL:		ØPV	С	10 Asbestos-ce	ement
1 Steel 3 Stainles	ss steel	5 Fiberglass	8 RM	P (SR)	11 Other (spec	ify)
2 Brass 4 Galvani	ized steel	6 Concrete tile	9 AB	S	12 None used	(open hole)
SCREEN OR PERFORATION OPENII	NGS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 Continuous slot (3)	Mill slot	6 Wire	wrapped		9 Drilled holes	
2 Louvered shutter 4 kg	Key punched 🔔 🔏	7 Toro	th cuty 7		10 Other (specify)	
SCREEN-PERFORATED INTERVALS	: From گر	≶ ft. to .		ft., Fr	om	ft. toft.
	From	<i></i> . π. το .		π.,⊢r	'om	π. το
GRAVEL PACK INTERVALS	i: From کی کی	ft. to .	21	ft., Fr	om	ft. toft.
	From	ft. to		ft., Fr	om	ft. to ft.
GROUT MATERIAL: 1 Neat	cement	Cement grout	3 Bento	nite , 4	4 Other	
Grout Intervals: From 1.9	ft. to	ft., From	. 2 ./ft.	to <i>l.¶</i>	ft., From	ft. to
What is the nearest source of possible	e contamination:			10 Live	estock pens 14	Abandoned water well
1 Septic tank 4 Late	eral lines	7 Pit privy		11 Fue	l storage 15	5 Oil well/Gas well
2 Sewer lines 5 Ces	s pool	8 Sewage lagoon		12 Fert	tilizer storage 16	Other (specify below)
Watertight sewer lines 6 See	page pit	9 Feedyard		13 Inse	ecticide storage	
Direction from well? Ws5+				How m	any feet? 20	
FROM TO	LITHOLOGIC LO	OG	FROM	то	PLUGGIN	G INTERVALS
0 31 TOPS	eil co					
	ay Stilt					
	SANC					
340 36 MEC +	o Coarsi San	12				
36 37.5 Coarsi	Sand				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
37.5 38.0 Lims SI	FONE					
CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATIO	N: This water well s	was 🝘 constru	cted (2) re-	constructed or (3) plugged	under my jurisdiction and was
completed on (mo/day/year)	4- 24-9	S. Jins water well t				knowledge and belief. Kansas
Water Well Contractor's License No.					d on (mo/day/yr)	
		, ,	_		// // //	
		MENTO.	France			
under the business name of Kyra INSTRUCTIONS: Use typewriter or ball poin of Health and Environment, Bureau of Wate	t pen. PLEASE PRESS FIR	MLY and PRINT clearly. F 0001. Telephone: 913-296	Please fill in blanks, i	by (sign underline or circ WATER WELL	cle the correct answers. Send to the	rree copies to Kansas Department cords.