

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: CHAUTAUQUA		NE 1/4 NE 1/4 NE 1/4	01	T 35 S	R 12 EW
Distance and direction from nearest town or city street address of well if located within city? from Blanning KS 2 miles South 1 7/8 miles West South side RR					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 155 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 55 ft. 2. 55 ft. 3. 55 ft.			
		WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was 7 gpm. Well water was 8 ft. after 155 hours pumping 8 gpm.			
		Bore Hole Diameter 8 in. to 155 ft., and 155 in. to 155 ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped X			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 in. to 135 ft., Dia 5 in. to 135 ft., Dia 5 in. to 135 ft.		7 Fiberglass 10 Asbestos-cement			
Casing height above land surface 5 in., weight 5 lbs./ft. Wall thickness or gauge No. 5		8 RMP (SR) 11 Other (specify)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		9 ABS 12 None used (open hole)			
1 Steel 3 Stainless steel 5 Fiberglass		6 Concrete tile			
2 Brass 4 Galvanized steel		7 PVC 10 Asbestos-cement			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped		6 Wire wrapped			
2 Louvered shutter 4 Key punched		7 Torch cut			
SCREEN-PERFORATED INTERVALS:		9 Drilled holes 10 Other (specify)			
From 155 ft. to 135 ft., From 155 ft. to 135 ft., From 155 ft. to 135 ft.		11 None (open hole)			
GRAVEL PACK INTERVALS:		12 None used (open hole)			
From 155 ft. to 20 ft., From 155 ft. to 20 ft., From 155 ft. to 20 ft.		13 Insecticide storage			
6 GROUT MATERIAL:		14 Abandoned water well			
1 Neat cement 2 Cement grout 3 Bentonite 4 Other		15 Oil well/Gas well			
Grout Intervals: From 155 ft. to 135 ft., From 155 ft. to 135 ft., From 155 ft. to 135 ft.		16 Other (specify below)			
What is the nearest source of possible contamination:		How many feet? 200 ft.			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage		13 Insecticide storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		17 Other (specify below)			
Direction from well?		18 Other (specify below)			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Silt			
1	50	Sand stone			
50	60	Shale			
60	70	Lime stone			
75	155	White sand stone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/5/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 501 This Water Well Record was completed on (mo/day/yr) 7/11/94 under the business name of Callier Water Well Service by (signature) Kenneth M. Callier					