**MW-8** WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 0049926 Section Number Township Number Range Number 1 LOCATION OF WATER WELL: Fraction Montgomery NW 1/4 NW 1/4 NE 1/4 R **16** 35 County: Distance and direction from nearest town or city street address of well if located within city? 3303 W. 8<sup>th</sup> St. - Coffeyville 2 WATER WELL OWNER: KDHE RR#, St. Address, Box# : 1000 SW Jackson St., Ste. 410 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Topeka, KS 66612 Application Number: City, State, ZIP Code : TOPERA, TO SOCIAL STATIC WATER LEVEL 14.55 ft. ELEVATION: 744.57 (TOC)

AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 23 ft. 2 14.85 ft. 3 ft. WELL'S STATIC WATER LEVEL 14.21 ft. below TOC measured on mo/day/yr 05/07/14 OFFICE Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8.25 in. to 25 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) w 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X CASING JOINTS: Glued Clamped 5 Wrought Iron 8 Concrete tile 5 TYPE OF BLANK CASING USED: Welded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Threaded 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 9.55 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

7 PVC 10 Asbestos-cement ATION MATERIAL:

Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

Salvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

ENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

3 Mill slot 6 Wire wrapped 9 Drilled holes

4 Key punched 7 Torch cut 10 Other (specify) 3 Stainless steel 4 Galvanized steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 

 2 Louvered shutter
 4 Key punched
 7 Torch cut
 10 Other (specify)

 SCREEN-PERFORATED INTERVALS:
 From
 9.55
 ft. to
 24.55
 ft. From
 ft. to
 ft.

 From
 ft. to
 ft. From
 ft. to
 ft.

 From
 8
 ft. to
 25
 ft. From
 ft. to
 ft.
 GRAVEL PACK INTERVALS: ft. From ft. to From ft. to 3 Bentonite 4 Other 1 Neat cement 2 Cement grout 6 GROUT MATERIAL: Grout Intervals From 1 ft. to 8 ft. From ft. to ft. From ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 4 Lateral lines 5 Cess pool 12 Fertilizer storage 16 Other (specify below) 8 Sewage lagoon 2 Sewer lines 3 Watertight sewer lines 6 Seepage pit 13 Insecticide storage 9 Feedyard .\_\_\_\_\_ Direction from well? How many feet? LITHOLOGIC LOG FROM PLUGGING INTERVALS TO FROM TO Ô 0.5 Silty Clay, dark brown to brown 0.5 23 Sandy Clay 23 24 24 25 Silty Clay, brown Survey Date: 05/23/14 Northing: 1459396.19 Easting: 2140100.78 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/yr) 05/07/14 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No.

531

This Water Well Record was completed on (mo/day/yr)

06/16/14

under the business name of GSI Engineering, LLC by (signature)

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W

Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.