WATE	R WEI	L RECORD	Form W	WC-5	Division of Wate	er Resources App. No	MW-1	
1 LOCATION OF WATER WELL:			Fraction		Section Number	Township No.	Range Number	
			SW 1/4 NW 1/4 NW		6	T 35 S	R 24	
Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information: Latitude: .37,02960			
from nearest town or intersection: If at owner's address, check here					Longitude: 94.83145 (in decimal degrees)			
10111 SE Highway 69 Baxter Springs, KS 66712					Elevation: 872.12			
					Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Polly C. Burcham Family Trust RR#, Street Address, Box #: 180 Stewart Dr.					Collection Method: ☐ GPS unit (Make/Model:)			
RR#, Street Address, Box #: 180 Stewart Dr. City, State, ZIP Code : Merritt Island, FL 32952					☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey			
Width Gilling, L 02002					Est. Accuracy: 📝	≤3 m, ☐ 3-5 m, ☐	5-15 m, >15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 15								
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 19							
obc.	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
KT	Pump test data: Well water wasft. after hours pumping gpm							
NV	EST. YIELDgpm. Well water wasft. after hours pumpinggpm							
w	W							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedfot Oil field water supply Dewatering Other (Specify below)								
SW SE Domestic Peetrot On reid water supply Dewatching Other (specify below)								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No								
S If yes, mo/day/yr sample was submitted								
Water well disinfected? Yes No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 2 in. to 5 ft., Diameter in. to ft. Casing height above land surface Flush in., Weight blockft., Wall thickness or gauge No. SCH 40								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Continuous slot								
SCREEN-PERFORATED INTERVALS: From								
From ft., to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: ✓ Neat cement ☐ Cement grout ✓ Bentonite ☐ Other								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Full Fuel storage Abandoned water well								
Watertight sewer lines Scepage pit Feedyard Fertilizer storage Oil well/gas well Direction from well South Distance from well 180'								
FROM	TO	LITHOLOG	CLOG	FROM			GGING INTERVALS	
0	1	Concrete, pavement	· · · · · · · · · · · · · · · · · · ·	41,0111		2 3 (32) 51 . 150		
1	3	Gravel, silty sand, gray	epinenty and the same and the s					
3	6	Silty Clay, moist to firm, gray						
6	8	Clay, some sift, gray w/ som	e brown, moist, soft			7		
8	12	Clay, gray-brown						
12	15	Sandstone, brown-red	THE STATE OF THE S					
		TOTAL PROPERTY OF THE PROPERTY						
			CONTROL OF THE CONTRO	 -				
			HW-			Commission of A 444 Commission of Commission	P-11/11/2004	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, 🗌 reconstructed, or 🗌 plugged								
under my jurisdiction and was completed on (mo/day/year) .4/16/14 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 704 This Water Well Record was completed on (mo/day/year) .5/27/.14								
under the business name of								
	Kansas De	partment of Health and Environ	ment, Bureau of Water, Geo	logy Section, 10	000 SW Jackson St., Suit	e 420, Topeka, Kansas	66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								