County: Cherokee Fraction NE NE NW SE Sec. 12 T 35 S R 25 (E/W	
CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5) (to rectify lacking or incorrect information) Owner: Hai-Ching Ying	
Location was listed as:	Location changed to:
Section-Township-Range: 12-355-25E	12-355-25E
Section-Township-Range: /2-355-25E Fraction (½½½): 5E SE SE	NE NE NW SE
Other changes: Initial statements: Public Water Supply	
Changed to: Domestic	
Comments:	
Verification method: Legal description, Cherokee County on line parcel search, and mapping tool & aerial photos on KGS website. Submitted by Verges Coolering Survey Det Brown 1930 Constant And Leganger 1930 (2013)	
parcel search, and mapping to	ool & aerial photos on initials: DRLdate: 4/26/2013
Sublimited by. Railsas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, R5 60047-37207	
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.	

Form WWC-5 WATER WELL RECORD KSA 82a-1212 ID No. LOCATION OF WATER WELL: Fraction Township Number Section Number Range Number SE County: Cherokee R 25 Distance and direction from nearest town or city street address of well if located within city? South of GAIENAKS ON WATER WELL OWNER: RR#, St. Address, Box # 2001 CONNECTICY Board of Agriculture, Division of Water Resources City, State, ZIP Code Application Number: 3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 2.00 ft. ELEVATION: AN "X" IN SECTION BOX: WIA - NF WELL WATER TO BE USED AS: (5 Public water supply) 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well 2 Irrigation 4 Industrial Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs sample was sub-- SF -Water Well Disinfected? (Yes) TYPE OF BLANK CASING USED: CASING JOINTS: Glued Clamped 5 Wrought iron 8 Concrete tile (Welded)..... 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 4 ABS 7 Fiberglass Threaded Blank casing diameter (25 0 in to ft., Dia in to ft TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-Cement 7 PVC 3 Stainless Steel 8 RMP (SR) 11 Other (Specify) 5 Fiberglass 1 Steel 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 8 Saw cut 11 None (open hole) 5 Guazed wrapped 9 Drilled holes 6 Wire wrapped Continuous slot 3 Mill slot 7 Torch cut 10 Other (specify)ft. 4 Key punched 2 Louvered shutter SCREEN-PERFORATED INTERVALS: **GRAVEL PACK INTERVALS:** From ______ft. to ______ft. to ______ft. From ft. to ft., From ft. to ft. 4 Other 6 - 94# SACKS POITIAND **GROUT MATERIAL:** 1 Neat cement) 2 Cement grout 3 Bentonite What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 7 Pit privy 15 Oil well/Gas well 1 Septic tank 4 Lateral lines 11 Fuel storage 2 Sewer lines 5 Cess pool (8 Sewage lagoon) 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? EAST How many feet? 175 FEET LITHOLOGIC LOG PLUGGING INTERVALS **FROM** FROM DirT CLAY & 20 LIMESTONE 327ellow Flint 190 White Flint Blue & Black FRINT CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10 0 3 and this record is true to the best of my knowledge and belief. Kansas by (signature) N MM under the business name of DrillinG CO

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.

18"ABOVE LAND SUFFACE LAND SUPACE LAND SURFACE Borehole cuttings -35' Reo Clay & Chert NEAT CEMENT GrOUT From 61/2 To 31/2 ELL BOTTOM of CASing EBore Dia. from Surface) to Bottom of Casing? 30' STATIC WATER Level FBore Dia. from Bottom & of Casing to Bottom of Well = 68" 165' LIMESTONE - 172 Yellow flint 190 White fint -200' Blue & Black flint