


1 LOCATION OF WATER WELL: County: Washington Fraction: S.W. 1/4 S.W. 1/4 S.W. 1/4 Section Number: 3 Township Number: T 3 S Range Number: R 1 EW
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: NATURAL GAS Pipeline Co. of America
 RR#, St. Address, Box #: P.O. BOX 298 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: GLASCO, KS. 67445 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 400 ft. ELEVATION: N.A.
 Depth(s) Groundwater Encountered 1. N.A. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: N.A. ft. below land surface measured on mo/day/yr
 Pump test data: Well water was N.A. ft. after hours pumping gpm
 Est. Yield N.A. gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 6" in. to 400 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)
Cathodic Protection
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass NONE Threaded
 Blank casing diameter N.A. in. to ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface N.A. in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From N.A. ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From N.A. ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 100 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
NO NEAR SOURCE
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	30'	Topsoil	3'	100'	Top 100' of bed is inactive. No
30'	40'	CLAY			
40'	140'	Shell with streaks of sandrock			
140'	320'	Clay with streaks of shell			
320'	400'				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-2-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 9-27-89 under the business name of Natural Gas Pipeline Co by (signature) Burke Jones