

USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

NW SW SW

1 Location of well:	County <b>Brown</b>	Township name <b>Powhattan</b>	Fraction <b>SW 1/4</b>	Section number <b>27</b>	Town number <b>35</b>	Range number <b>R 15 E</b>
Distance and direction from nearest town or city: <b>5 W Powhattan KS</b>			3 Owner of well: <b>I-Com - JBN Telephone Co</b> <b>Box 4E WETMORE, KANS.</b>			
Street address of well location if in city:			Address: <b>Box 4E WETMORE, KANS.</b>			
Locate with "X" in section below: N W E S 1 Mile			Sketch map: 50'		4 Well depth: <b>120</b> ft. Date of completion Well diameter <b>12</b> in. <b>3-24-75</b>	
2 Type and color of material			From		To	
			Top Soil 0-3 - Gray Clay		3 6	
			Brown Clay 6-10 - Brown Sandy Clay		10 15	
			Gray Clay 15-19 - Yellow Lime Stone		19 23	
			Tan Shale 23-24 - Brown Limestone		24 27	
Black Shale 27-28 - Gray Shale			28 30		5 Screen: Manufacturer <b>PumpCo</b> Type <b>PVC</b> Dia. <b>6"</b> Slot/gauge <b>0.80</b> Length <b>10'</b> Set between <b>95</b> ft. and <b>105</b> ft. Fittings: Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material <b>1/4" to 1/2"</b>	
Tan Shale 30-31 - Gray Lime Stone			31 37		9 Static water level: <b>No measurement</b> _____ ft. below land surface Date _____	
Gray Shale 32-44 - Gray Lime Stone Soft			44 49		10 Pumping level below land surfaces: _____ ft. after _____ hrs. pumping _____ g.p.m. _____ ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield <b>30</b> g.p.m.	
Red Shale 49-51 - Tan Limestone			51 53		11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date _____	
Soft Yellow lime 53-57 - Gray Shale			57 60		12 Well head completion: <input type="checkbox"/> Pitless adapter <input checked="" type="checkbox"/> 24" Inches above grade	
Black Shale 60-67 - Gray Limestone			67 68		13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> _____ Depth: From <b>0</b> ft. to <b>10</b> ft.	
Gray Shale 68-85 - Soft Gray lime			85 107		14 Nearest source of possible contamination: ft. <b>600</b> Direction <b>NORTH</b> Type <b>SEPTIC TANK</b> Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
" " 107-116 - Gray Limestone			116 117		15 Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.m.p. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
Gray Shale			117 120		17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Strader Drilling Co. Inc. #182</b> Business name _____ License No. _____ Address <b>RR1-HY. 75N HOLTON, KANS</b> Signed <b>Dele Rahum</b> Date <b>4-10-75</b> Authorized representative	
16 Remarks: elevation <b>1185'</b> Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						

BR= 1166