WATER WELL R	ECORD Form Correction Chang	WWC-5		ision of Water ources App. No	1	Well ID
1 LOCATION OF W		Fraction		tion Number		
County: Brow		NE 145W 145W 14	l l	13	T 3 S	R /5 ⊠ E □ W
2 WELL OWNER: La	ast Name: Spanaler	First: Shane		ral Address v	where well is located	(if unknown, distance and
Business:			direction from	nearest town or	intersection): If at owner	r's address, check here:
Address: 655 220 th st. 2 mi. south, & mi. east from Farriew.						ast from Farriew,
City: Farview	State: KS	ZIP: 66425		,	,	Ks,
3 LOCATE WELL	T		124			
WITH "X" IN	4 DEPTH OF COM	MPLETED WELL: .				(decimal degrees)
SECTION BOX:	Depth(s) Groundwater		Longitude:			
2)					☐ WGS 84 ☐ NAI	
below land surface, measured on (mo-day-yr)					for Latitude/Longitude	-
					(WAAS enabled?)
NW NE	Pump test data: Well water was ft.				nd Survey \[\begin{array}{c} \text{Topogration} \\ \ext{Topogration} \\	
$ \mathbf{w} - \mathbf{E} $	after hour		Online Mapper:			
' '	Well water was ft.					
after hours pumping			gpm	6 Florest	ion: A	□ Cround Lovel □ TOC
Estimated Yield:? \$gpm				6 Elevation:ft. Ground Level TOC		
S Bore Hole Diameter:			ft. and	Source:		
mile		in. to	it.			
7 WELL WATER TO 1. Domestic:		ator Cumply, wall ID		10 🗆 0:1	Field Water Cumples 1	200
Household		ater Supply: well ID ng: how many wells?		10. ☐ Oil Field Water Supply: lease		
Lawn & Garden		techarge: well ID			ed Uncased 0	
Livestock		ng: well ID			ermal: how many bores	
2. Irrigation		tal Remediation: well ID			sed Loop 🔲 Horizont	
3. Feedlot		ge 🔲 Soil Vapor F	Extraction	b) Open Loop Surface Discharge Inj. of Water		
4. Industrial	☐ Recovery	☐ Injection		13. 🔲 Oth	er (specify):	
Was a chemical/bacter	iological sample subn	nitted to KDHE?	Yes 💆 No	If yes, date	sample was submitte	ed:
Water well disinfected?	☐ Yes No			•	-	
8 TYPE OF CASING	USED: ☐ Steel ☑ PV	C Other	CASI	JG IOINTS:	MClued Clemner	d □ Welded □ Threaded
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter fin. to fi						
Casing diameter	in. to 4.3. ft.,	, Diameter	in. to	ft., Diame	eter in. to	ft.
Casing height above land s	surface ir	n. Weight	in. to	ft., Diame	eterin. to	ft.
Casing height above land s TYPE OF SCREEN OR	surface	n. Weight TERIAL:	in. to	ft., Diame Wall thick	eterin. to ness or gauge No	ft. 5DR 2J
Casing height above land s TYPE OF SCREEN OR ☐ Steel ☐ Stair	surface	n. Weight TERIAL: rglass ⊠ PVC	in. to lbs./ft.	ft., Diame Wall thickr ☐ Othe	eter in. to	ft. 5DR 2J
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv	surface	n. Weight TERIAL: rglass	in. to	ft., Diame Wall thickr ☐ Othe	eterin. to ness or gauge No	ft. 5DR 2J
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR	surface	n. Weight	in. to	ft., Diame Wall thickr Othe	eterin. to	5DR 2]
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot	surface	n. Weight	in. to	ft., Diamo Wall thickr Dotho	eterin. to	5DR 2]
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter	surface	n. Weight	in. to	ft., Diame Wall thickr Othe Prilled Holes Tone (Open Ho	eterin. to ness or gauge No er (Specify) Other (Specify)	ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE	surface	n. Weight	in. to	Wall thicks Wall thicks Other orilled Holes Hone (Open Ho	eterin. to	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC	surface	n. Weight	in. to	Wall thicks Wall thicks Other Prilled Holes Ione (Open Ho ft. to	eter	ft. 5000 21
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC	surface	n. Weight	in. to	Wall thickr Wall thickr Other Prilled Holes Jone (Open Ho fi. to Other	eter	ft. 5000 21
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From	surface	n. Weight	in. to	Wall thickr Wall thickr Other Prilled Holes Jone (Open Ho fi. to Other	eter	ft. 5000 21
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: dauze Wrapped To Vire Wrapped San n 35 ft. to 53 Cement grout Be ft., From	in. to	wall thickr Wall thickr Other Orilled Holes Jone (Open Ho fi. to Other The right to the control of the con	eter	ft. 5000 21 ft. ft. ft. ft. ft. ft. ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: dauze Wrapped Sam n. 35 ft. to 35 Cement grout Be ft., From	in. to	Wall thickr Wall thickr Other Prilled Holes Jone (Open Ho fi. to Other	eter	ft. 5000 21
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines Watertight Sewer Line	surface	n. Weight	in. to	wall thickr Wall thickr Other orilled Holes Ione (Open Ho	eter	ft. 5000 21
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify)	surface	n. Weight TERIAL: rglass	in. to	orilled Holes Ione (Open Ho In to Other In to Other In to Other In to Other It to Other In the Storage In the S	cr (Specify)	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well?	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: dauze Wrapped Sam n 35 ft. to 53 Cement grout Be ft., From Pit Privy Sewage Lag t Feedyard Distance from we	in. to	wall thickr Wall thickr Othe c) orilled Holes Jone (Open Ho fi. to other	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well?	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: dauze Wrapped Sam n 35 ft. to 53 Cement grout Be ft., From Pit Privy Sewage Lag t Feedyard Distance from we	in. to	wall thickr Wall thickr Othe c) orilled Holes Jone (Open Ho fi. to other	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: dauze Wrapped Sam n 35 ft. to 53 Cement grout Be ft., From Pit Privy Sewage Lag t Feedyard Distance from we	in. to	wall thickr Wall thickr Othe c) orilled Holes Jone (Open Ho fi. to other	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: dauze Wrapped Sam n 35 ft. to 53 Cement grout Be ft., From Pit Privy Sewage Lag t Feedyard Distance from we	in. to	orilled Holes Formula to to the control of the cont	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12 12 21	surface	n. Weight	in. to	orilled Holes Formula to to the control of the cont	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 12 12 21 38	surface	n. Weight	in. to	orilled Holes Formula to to the control of the cont	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest seurce of possible Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12 12 21 38 40	surface	n. Weight	in. to	orilled Holes Formula to to the control of the cont	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 12 12 21 38 38 40 40 40 49	Surface	n. Weight	in. to	orilled Holes Formula to to the control of the cont	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12 12 21 38 40 40 49 52	surface	n. Weight TERIAL: rglass PVC crete tile None u RE: lauze Wrapped Sam n 35 ft. to 5 Cement grout Be ft., From Pit Privy Sewage Lag t Feedyard Distance from we GIC LOG	in. to	orilled Holes Formula to to the control of the cont	eter	ft. to ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12 12 21 38 40 40 49 52 52 54	surface	n. Weight	in. to	orilled Holes Ione (Open Home) In the too the first too th	eter	ft. to ft ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12 12 21 38 40 40 49 52 52 54	surface	n. Weight	in. to	orilled Holes Ione (Open Home) In the too the first too th	eter	ft. to ft ft.
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest seurce of possible Seer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 12 12 21 21 38 38 40 40 49 49 52 52 54 54 625 11 CONTRACTOR'S	surface	n. Weight	in. to	orilled Holes Ione (Open Holes) Ione (Open Holes) Ione (The to the to the to the to the to the to the Toles	cr (Specify)	ft. to
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest seurce of possible Seer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 12 12 21 21 38 38 40 40 49 49 52 52 54 54 625 11 CONTRACTOR'S under my jurisdiction an	surface	n. Weight	in. to	wall thickr Wall thickr Wall thickr Other Orilled Holes Ione (Open Ho Ione ft. to Other	constructed, recottrue to the best of m	ft. to ft
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest seurce of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 0 3 1 3 12 12 21 21 38 40 40 49 49 49 52 54 625 11 CONTRACTOR'S under my jurisdiction and Kansas Water Well Con under the business name	surface	m. Weight TERIAL: rglass PVC crete tile None u RE: lauze Wrapped Sam m. 36 ft. to 5 Cement grout Be ft., From Pit Privy Sewage Lag t Feedyard Distance from we GIC LOG S CERTIFICATION mo-day-year) 10-12 6-27 This Wa Je 1 Oct 11 129	in. to	orilled Holes Ione (Open Ho In to Other In	cr (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. to ft. cide Storage oned Water Well cll/Gas Well PLUGGING INTERVALS onstructed, or plugged y knowledge and belief. ear) 10-13-15

KSA 82a-1212

Revised 9/10/2012

Visit us at http://www.kdheks.gov/waterwell/index.html