

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Brown	SW ¼ SE ¼ NW ¼	28	T 3S	R 16 E

Distance and direction from nearest town or city street address of well if located within city?

100' N of Main on E side of Center

2 WATER WELL OWNER:	KDHE-BER	RR#, St. Address, Box # :	Forbes Field, Building 740	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Topeka, Kansas 66620	Application Number:		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL . . . 66 ft. ELEVATION:			
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 1204.6 ft.			
	WELL'S STATIC WATER LEVEL 11.6 ft. below land surface measured on mo/day/yr 1/23/95			
	Pump test data: Well water was ft. after hours pumping gpm			
	Est. Yield . . . NA . . . gpm: Well water was ft. after hours pumping gpm			
	Bore Hole Diameter 8 in. to 73 ft., and in. to ft.			
WELL WATER TO BE USED AS:				
5 Public water supply	8 Air conditioning	11 Injection well		
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X		

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded X
Blank casing diameter 4 in. to 56 ft., Dia in. to ft., Dia in. to ft.	Casing height above land surface -4.6 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS:				
From 56 ft. to 66 ft., From ft. to ft.	From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:				
From 54 ft. to 73 ft., From ft. to ft.	From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From 0 ft. to 40 ft., From 40 ft. to 54 ft., From ft. to ft.	What is the nearest source of possible contamination:			
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	Grain Storage
Direction from well? NW	How many feet? 200			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.5	Clay, Dark Brown			MW6
3.5	10	Clay, Gray Brown			GeoCore # 113
10	30	Clay, Red Brown			Flush-mount Cover
30	40	Clay, Light Gray			KDHE #
40	60	Clay, Red Brown			Tag # 00117045
60	66	Clay, Light Gray Brown			
66	73	Shale, Light Gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 1/23/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/15/95 under the business name of GeoCore Services, Inc. by (signature) <i>Dale Holt</i>

* INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.