No. of the second	√ WATE	RIWELL RECORD	Form W	WC-5 KSA	82a-1212	•	X
LOCATION OF WATER WELL:	Fraction 5 6	4	//	Section Num	ber Townsh	p Number	Range Number
iny: Brown	1/4		<u>58 ¼</u>	12	јт	3 <sub>S</sub>	R /7 (E)W
Ance and direction from nearest to	. 11	ddress of well if lo	cated within	city?			_
	obiheon Ks	-					
WATER WELL OWNER: ( )	1 .	<b>^</b>	Box	65			<b></b>
#, St. Address, Box # : /// v, State, ZIP Code	lax E. O	0 Hjen	Haw	atha Ks	Board Applic	of Agriculture, ation Number:	Division of Water Resource
OCATE WELL'S LOCATION WITH N "X" IN SECTION BOX:	DEPTH OF C	OMPLETED WELL	L <b>ジ</b> ス	ft. ELI	EVATION:	714 PH	above see bu
N	Depth(s) Ground	water Encountered	່ 1. ອຳ		ft. 2	ft	3
		WATER LEVEL .			surface measure		
NW NE							umping . 1. 8 gpl
							umping gpi n. to
w	C i	FO BE USED AS:					
	1 Domestic	GFeedlot		: water supply Id water supply	8 Air condition 9 Dewatering	•	Injection well Other (Specify below)
SW SE	2 Irrigation	4 Industrial			ly 10 Monitoring		Other (Specify below)
	1/ *	bacteriological sam		-	- /-	1 V	s, rpo/day/yr sample was su
<u> </u>	mitted	baotonological ban	ipio oubiliillo	, to bopartmon	Water Well Disin		No No
TYPE OF BLANK CASING USED:		5 Wrought iron	(8 (	Concrete tile			ed Clamped
1 Steel 3 RMP (		6 Asbestos-Cem		Other (specify b			ded
2 PVC 4 ABS		7 Fiberglass					aded
nk casing diameter	in_ to 5.	2 ft., Ďia	<u></u> ,	in. to	.ft., Dia		in. to
sing height above land surface	. <b>38</b>	.in., weight	320	<b>(</b>	lbs./ft. Vall thickn	ess or gauge N	۱۰
PE OF SCREEN OR PERFORATION	ON MATERIAL:		-	7 PVC	10	Asbestos-cem	ent
1 Steel 3 Stainle	ss steel	5 Fiberglass		8 RMP (SR)	11	Other (specify	) <u></u>
2 Brass 4 Galvan	nized steel	6 Concrete tile		9 ABS	1,5	None used (o	pen bele
REEN OR PERFORATION OPEN	INGS ARE:	5 0	auzed wrapp	ped	8 Saw cut		11 None (open hole)
1 Continuous slot 3	Mill slot	6 V	Vire wrapped		9 Drilled ho	les	
2 Louvered shutter 4	Key punched	7 T	orch cut		10 Other (sp	ecify)	
REEN-PERFORATED INTERVALS	3: From	ft. <sup>-</sup>	to	ft.,	From	ft.	tof
	From	ft.	to	ft.,	From	$\dots$ . ft.	tof
GRAVEL PACK INTERVALS	S: From	ft. :	to	ft.,	From	$\dots \dots ft.$	tof
	From	ft.			From	ft.	
		2 Cement grout	_	Bentonite	4 Other		
		<b>9</b> ft., From				n	
nat is the nearest source of possible 1 Septic tank 4 Late	eral lines	7 Pit privy			ivestock pens uel storage		Abandoned water well Dil well/Gas well
	erar intes ss pool	8 Sewage			ertilizer storage		Other (specify below)
3 Watertight sewer lines 6 See	-	9 Feedya	-		ertilizer storage isecticide storage	10 (	
ection from well?	abage pit	2 Teedya			many feet?	1200	*
ROM TO	LITHOLOGIC	LOG	FRO	· · · · · · · · · · · · · · · · · · ·	Thursy 100t:	PLUGGING	INTERVALS
B 3 BLAC	X 5/LT4	TOPSO	16				
3 11 SANO	IV, CLA	4					
T1 2/ GRAU	SILTUI	LLAG					
21 38 864	2 CLA	4 /					
38 46 ZA	26E B	LAE-G	RAY	_	1		
SANO	+ GRAD		VARG	PROD	aCTIVE		
46 52 BLUE	- SHAL	<u> E</u>			•		
						· · · · · · · · · · · · · · · · · · ·	
CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATI	ON: This water we	ell was (1) co				
	L-984.						nowledge and belief. Kans
ter Well Contractor's License No.	لا في مر	Co This Wat	er Well Reco			) <b>/</b>	70
er the business name of	PLEWELL	WELL B	ORING	by (si	gnature) Lev	4 Nras	well
INSTRUCTIONS: Use typewriter or ball poir of Health and Environment, Bureau of Wate	nt pen. PLEASE PRESS F	FIRMLY and PRINT clea	rly. Please fill in	blanks, underline or	circle the crrect answ	rs. Bene too three	copies to Kansas Department

a 11

0071