

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number				
County: BROWN		SW ¼ SW ¼ SW ¼	14	T 3 S	R 17 EW				
Distance and direction from nearest town or city street address of well if located within city? 2 south, 4 west of Robinson									
2 WATER WELL OWNER: Floyd Lambert RR#, St. Address, Box #: Rt. 5 Box 158 City, State, ZIP Code: Hiawatha, KS 66434									
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 78' ft. ELEVATION:							
N <table border="1" style="margin:auto; width:100px; height:100px;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE</td></tr></table> S		NW	NE	SW	SE	Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.			
		NW	NE						
SW	SE								
WELL'S STATIC WATER LEVEL 28' ft. below land surface measured on mo/day/yr 1-10-89 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 40 GPH xprc Well water was ft. after hours pumping gpm Bore Hole Diameter 12" in. to ft., and in. to ft.									
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		Welded							
2 PVC 4 ABS		Threaded							
Blank casing diameter 5" in. to 0-35 ft., Dia 5" in. to 41-45 ft., Dia 5" in. to 51-78 ft.		Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. .258							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)							
2 Louvered shutter 4 Key punched 7 Torch cut									
SCREEN-PERFORATED INTERVALS: From 35 ft. to 41 ft., From ft. to ft.									
From 45 ft. to 51 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 24 ft. to 78 ft., From ft. to ft.									
From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From 4 ft. to 24 ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard									
Direction from well? E		How many feet? 900							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	36	Clay-Brown							
36	38	Fine Sand-Coarse Sand-Brown							
38	47	Clay-Brown							
47	48	Fine Sand-Brown							
48	78	Shale-Grey							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-10-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 2-9-89 under the business name of STRADER DRILLING CO., INC. by signature Dale Strader									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									