WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	DONIPHAN Fraction NE 1/4 NE1/4 NE			Section number		Township n	umber	Ran	ge number	_		
1. Location of well:			1/4		3	т	3	S R	20	E)W		
2. Distance and direct	İ	er of well:	:	RoyRMo	oere							
south of Fanning, Kansas. R.R Street address of well location if in city: City,					ode.	Troy,		as 6	6087			
4 Locate with "X" in section below: Sketch map:						_			•	2/21	/77	
DRAINAGE							th <u>43</u> (Bore-	hole	is 42	" to	,]
1 1 WELL							e tool Ro					
NW	1	1		8. Use: X				everse rotary				
w i	\downarrow	1)			Irrigation _							
T							Lawn _			Other		
ORAINAGE							Mate colon Welded		ht: Above face	or below 30 in.		
S	RMP	_ PVC_	¦We	ight2(00_lbs./ft.							
1 1 Mi		COUNTY	ND	r		Dia 30 in.	. to 43 ft.			: inches or 2. TN		
5. Type and color of	material			From	То	10. Screen:			ye 140			
Hard -	dry windhlown w	/brown streak	S	0	12							
Hard - dry windblown w/brown streaks					17	Type Slot/gauze_			gth			
Same - But some softer					17	Set between		ft.a .ft.and	nd	ft.		
Very light windblown w/brown & black					31	Gravel pack	c? Si:		f material		:	
streaks						11. Static w			- 20/	mo./day/yr.		
Sandy windblown - very soft					34		ft. below lar			10/77		
Sandy w		31	<u> </u>	_31_fi.	after _2	hrs. p	umping	30 g.p.m.				
Large sand and gravel w/boulders as					43	_	after 4 aximum yield		omping —	30. g.p.m. g.p.m. :		
large as plates, very, very, productive						13. Water so				mo./day/yr.		
Hard, blue, shale						Yes	<u>X</u> No	Date				
naru, b	orue, share	150		43		14. Well he	ad completions adapter	on:	Inches ab	ove grade		
		· · · · · · · · · · · · · · · · · · ·				15. Well gro				g	۱ ،	
						With:_X_	Negt cement	Be	ntonite	Concrete		
						Depth: From		t. to	tamination	******	W	7
										<u>SEPTIC</u>		
							ected upon c		Not instal		1/2	>
						17. Pump: Manufacture	er's name		_ Not Instal	rea	0 .	1
	the late of the second						er			Volts	⟨	1
						Length of dr Type:	rop pipe —	"	. capacity <u> </u>	g.p.m.	'	7
						Subr	mersible		Tui		ļ ₁	
	(Use a second	heet if needed)				Jet Cen	trifugal			ciprocating her	Se .	_
18. Elevation: 7/ / installed by customer. He knows and understands this is a regulation.							well contrac			_] M	,
							as drilled un ne best of my	, ,		•	_	
							EWELL				温点	
HIII SIGN HERE						Business nam	me Amit	y, M	0 64	422 No.	S =	
Upland y J M							ruy po	Plu	ell .	Date 3/10/	1227	i
Valley	1 A C Tray XI	Moore.		···		1 6	Ayrnoriz	y represen	iutive	10165	ٵ؞۪ٳڮ	, !
Forward the white, blu	ue and pink copies to the Department	at Health and Environment							Form	WW.C-5	, , ,	į.