

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County	Fraction	Section number	Township number	Range number
	Doniphan	NW 1/4 SE 1/4	27	T 3 S R 20 E	
2. Distance and direction from nearest town or city: .4 E OF		3. Owner of well: RAY HOVERSON			
Street address of well location if in city: MORAY		R.R. or street:			
		City, state, zip code: RRI Troy KS. 66097			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 9-8-77	
				Well depth 140 ft.	
				7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dig <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
				8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
				9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 29 in. RMP <input type="checkbox"/> PVC 9L Weight 2.58 lbs./ft. Dia. 5 in. to 140 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 279	
5. Type and color of material		From	To	10. Screen: Manufacturer's name	
Top Soil		0	3	Dumco, MPJ	
Clay, Blue		3	55	Type PVC Dia. 5	
Shaley, Limestone		55	80	Slot gauge .020 Length 60	
Sandstone		80	85	Set between 40 ft. and 100 ft.	
Limestone, grey, shale, blk, grey		85	140	Gravel pack? <input checked="" type="checkbox"/> Size range of material .030x.060	
				11. Static water level: mo./day/yr. 30 ft. below land surface Date 9-8-77	
				12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 2 g.p.m.	
				13. Water sample submitted: mo./day/yr. Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Date	
				14. Well head completion: 240 Pitless adapter 29 inches above grade	
				15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 5 ft. to 15 ft.	
				16. Nearest source of possible contamination: ft. 400 Direction SE Type SEPTIC Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
				17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation: 1069		19. Remarks:		20. Water well contractor's certification:	
Topography: <input checked="" type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley		owner to install slab		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. STRADER Dalg Co Inc 182 Business name License No. Address Highton, KS Signed Dale Highton Date 9-13-77 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

BR = 1014 V = 1039