WATER WELL RE	CORD	Form V	WWC-5		Thirdsian at Mate	- Danassan (N		
1 LOCATION OF W. County: DON'P	TER WELLS Fr	action		Sec	ction Number	TRESOURCES App. No.	Range Number	
Street/Rural Address	of Well Location; if un	1/4 NW/4 S	W/4 5h		33	T 3 S	R ZO NE DW	
from nearest town or	intersection: If at own	er's address, che	ck here	Lat	titude: 3.2.7	129/9 (GPS) ir	itormation; (in decimal degrees)	
200	Lo	Global Positioning System (GPS) information: Latitude: 39,742,74 (in decimal degrees) Longitude: -095.11887116 (in decimal degrees)						
Bendena, K5, 66008 Elevation: Datum: WGS 84, NAD 83, NAD 27								
RR#, Street Address, Box #: 5top 0513 Room 4714-5 City, State, ZIP Code : 1400 Independence Avenue see Digital Map/Photo, Topographic Map, Land Survey								
3 LOCATE WELL	EBINGITON, DC	20250 - 0	0.5 / 3	Est.	Accuracy: \(<	3 m, 3-5 m, 3	5-15 m, >15 m	
WITH AN "X" IN SECTION BOX:	The same of the sa							
N N N N N N N N N N N N N N N N N N N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
	Pump test data: Well water wasft. after hours pumping gram							
W NW NB B	EST. YIELDgpm. Well water was ft. after hours pumping. gpm Bore Hole Diameter 1 in to 20 ft., and in to ft.							
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well								
was a chemical/bacteriological sample submitted to Department? Yes No								
If yes, mo/day/yr sample was submitted								
CASING JOINTS: Glued Glammed Welded Williams								
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight 32 lbs./ft., Wall thickness or gauge No. 5.6.4.40								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.								
SCREEN-PERFORATEI	DINTERVALS: From	17	ft. to	7	ft., From	ft. to	o ft.	
GRAVEL PACK	From INTERVALS: From	2/h	ft. to		ft., From	ft. to	ft	
	rrom		tt. to		ft., From	ft ta	n. ft	
6 GROUT MATERIAL Grout Intervals: From	: LI Neat cement	🔲 Cement grou	t 🔯 Bent	onite [Other			
What is the hearest source		ion:	a ,	. it. to	tt., J	From	ft. toft.	
Septic tank Sewer lines	Lateral lines	Pit privy	Livestock	pens	Insecticide s	torage	r (specify below)	
Watertight sewer lin	Cesspool comes Seepage pit	Feedvard	Fertilizer	.ge storage ·	Abandoned v	25	***************************************	
Direction from well	LITHOLOGIC LC	\ <u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>						
	clay	70	FROM	TO	LITHU, LO	G (cont.) or PLUC	GGING INTERVALS	
	/							
		odnikaran yakalikan katan kata wa manakan wa manaka katan katan katan katan katan katan katan katan katan kata				on the state of th	and the state of t	
						erennen i Santonin di Residenti Santoni spesi epitalisty i appende y <u>antico</u> pie i b _{ere}		
		and the second s						
				····		and the same of the same and th		
7 CONTRACTOR'S OR	LANDOWNER'S CE	RTIFICATION	V: This wat	er well u	was M considered	ted Treconde	sted or Caluman	
7 CONTRACTOR'S OR under my jurisdiction and w	vas completed on (mo/	day/year)//./	2/14 a	nd this r	ecord is true to	the best of my kno	owledge and belief.	
under the business name of	CASCADE	Drilling K	vater Well Is	w broos.	as completed or	n (mo/day/year)		
Telephone 785-296-5524. Send	one copy to WATER WE	Tionment Bureau c	it Water Gent	any Section	m 1000 CW India	on C4 Culta ADA To	l. 17 C/C10 10 CH	
http://www.kdheks.gov/waterwell/ .SA 82a-1212	index.html.						200, 00 01	