

MW-3

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 36 Township Number T 03 S Range Number R 22 EW
 County: Doniphan

Distance and direction from nearest town or city street address of well if located within city?

2009 Roseport Road, Elwood

2 WATER WELL OWNER: Textron, Inc.
 RR#, St. Address, Box # : 100 Virginia Center Parkway
 City, State, ZIP Code : Providence, RI 02903
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
-NW-		-NE-	
	X		
-SW-		-SE-	
W			E
S			

4 DEPTH OF COMPLETED WELL 22.57 ft. ELEVATION: 815.24
 Depth(s) Groundwater Encountered 1 17.55 ft. 2 - ft. 3 - ft.
 WELL'S STATIC WATER LEVEL 17.55 ft. below land surface measured on mo/day/yr 01/24/05
 Pump test data: Well water was - ft. after - hours pumping - gpm
 Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-3

Was a chemical/bacteriological sample submitted to Department? Yes - No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes - No NA

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped -
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded -
 Blank casing diameter 2 in. to 13 ft. Dia - in. to - ft. Dia - in. to - ft. Dia
 Casing height above land surface -0.89 in., weight - lbs./ft. Wall thickness or gauge No. Sch. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) -
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) - ft.
 SCREEN-PERFORATED INTERVALS: From 23 ft. to 13 ft., From - ft. to - ft.
 GRAVEL PACK INTERVALS: From 23.5 ft. to 10.5 ft., From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -
 Grout Intervals: From 10.5 ft. to 2 ft., From - ft. to - ft., From - ft. to - ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 Direction from well? NW How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Asphalt			
1	5.5	silty clay (CL)			
5.5	23.5	silt/very fine sand (ML)			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/24/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 650 This Water Well Record was completed on (mo/day/yr) 03/04/05 under the business name of Deffenbaugh Field Services by (signature) [Signature]